

RockFIIT API Documentation

Louis Doherty

API Server IP Address : <https://rockFIITapi.lousterd.repl.co> (Testing site)

exercises API

Purpose

The mobile app client is delivered with a local copy of the exercise library, and this API enables the local database to be updated at regular intervals. This enables centralized distribution of data to the mobile app installation.

Request

URL-path: “/exercises”

Method Type: GET

Authentication required: No

Body of request: Empty

Response

The exercise route API sends a response in JSON format:

```
{
  'info' : <text>,
  'data' : <data>
}
```

The 'info' field is a text field and will always be present. When a successful response is sent (status code 200) , it will remain empty. However, when an unsuccessful response is sent (status code 5xx), it may contain the error information regarding the issue.

The 'data' field contains the exercise library as a list of lists, with each of the inner lists representing a row of the table. The elements of the list will be ordered corresponding to the table's field order.

addUser API

Purpose

This API creates a new user in the userTable within the database.

Request

URL-path: “/addUser”

Method Type: POST

Authentication required: No

Body of request: Contains user information

Format:

```
{
  'userName'   : <text>,
  'password'   : <text>,
  'firstName'  : <text>,
  'weight'     : <real>
}
```

The 'userName' field is a text field that contains the email address of a new user.

The 'password' field is a text field that contains the plaintext password of the user. Because the request uses HTTPS, the data is secure while being sent to the server. The server generates a unique salt for each new user and hashes the password, then stores that hashed password in the centralized database.

The 'firstName' field is a text field that contains the first name of the user.

The 'weight' field is a real field, which in SQL translates to any floating point number. This is the user's current weight in pounds.

Response

The addUser route API sends a response in JSON format:

```
{
  'info' : <text>,
  'data' : False
}
```

The 'info' field is a text field and will always be present. When a successful response triggered by the creation of a new user is sent (status code 201), it will remain empty. However, when an unsuccessful response is sent (status code 5xx), it may contain the error information regarding the issue.

The 'data' field is a False boolean as it is not utilized in this response.

changePassword API

Purpose

This API updates a user's password in the userTable within the database.

Request

URL-path: "/changePassword"

Method Type: POST

Authentication required: No

Body of request: Contains user information

Format:

```
{
  'userName'   : <text>,
  'oldPwd'     : <text>,
  'newPwd'     : <text>,
}
```

The 'userName' field is a text field that contains the email address of a user.

The 'oldPwd' field is a text field that contains the current plaintext password of the user. Because the request uses HTTPS, the data is secure while being sent to the server.

The 'newPwd' field is a text field that contains the user's new plaintext password. Because the request uses HTTPS, the data is secure while being sent to the server. This will become the user's new password to login.

Response

The addUser route API sends a response in JSON format:

```
{
  'info' : <text>,
  'data' : False
}
```

The 'info' field is a text field and will always be present. When a successful response triggered by the updating of the user's password is sent (status code 201), it will remain empty. However, when an unsuccessful response is sent (status code 5xx), it may contain the error information regarding the issue.

The 'data' field is a False boolean as it is not utilized in this response.