

# **Typechecking With PropTypes**

#### Note:

React.PropTypes has moved into a different package since React v15.5. Please use the prop-types library instead.

We provide a codemod script to automate the conversion.

As your app grows, you can catch a lot of bugs with typechecking. For some applications, you can use JavaScript extensions like <u>Flow</u> or <u>TypeScript</u> to typecheck your whole application. But even if you don't use those, React has some built-in typechecking abilities. To run typechecking on the props for a component, you can assign the special propTypes property:

```
import PropTypes from 'prop-types';

class Greeting extends React.Component {
   render() {
     return (
          <h1>Hello, {this.props.name}</h1>
     );
   }
}

Greeting.propTypes = {
   name: PropTypes.string
};
```

PropTypes exports a range of validators that can be used to make sure the data you receive is valid. In this example, we're using PropTypes.string. When an invalid value is provided for prop, a warning will be shown in the JavaScript console. For performance reasons, propTylis only checked in development mode.

#### **PropTypes**

Here is an example documenting the different validators provided:

```
import PropTypes from 'prop-types';
MyComponent.propTypes = {
  // You can declare that a prop is a specific JS type. By default, these
  // are all optional.
  optionalArray: PropTypes.array,
  optionalBool: PropTypes.bool,
  optionalFunc: PropTypes.func,
  optionalNumber: PropTypes.number,
  optionalObject: PropTypes.object,
  optionalString: PropTypes.string,
  optionalSymbol: PropTypes.symbol,
  // Anything that can be rendered: numbers, strings, elements or an array
  // (or fragment) containing these types.
  optionalNode: PropTypes.node,
  // A React element.
  optionalElement: PropTypes.element,
  // You can also declare that a prop is an instance of a class. This uses
  // JS's instanceof operator.
  optionalMessage: PropTypes.instanceOf(Message),
  // You can ensure that your prop is limited to specific values by treating
  // it as an enum.
  optionalEnum: PropTypes.oneOf(['News', 'Photos']),
  // An object that could be one of many types
  optionalUnion: PropTypes.oneOfType([
   PropTypes.string,
   PropTypes.number,
   PropTypes.instanceOf(Message)
  1),
  // An array of a certain type
  optionalArrayOf: PropTypes.arrayOf(PropTypes.number),
  // An object with property values of a certain type
  optionalObjectOf: PropTypes.objectOf(PropTypes.number),
```



```
// An object taking on a particular shape
 optionalObjectWithShape: PropTypes.shape({
   color: PropTypes.string,
   fontSize: PropTypes.number
 }),
 // You can chain any of the above with `isRequired` to make sure a warning
 // is shown if the prop isn't provided.
 requiredFunc: PropTypes.func.isRequired,
 // A value of any data type
 requiredAny: PropTypes.any.isRequired,
 // You can also specify a custom validator. It should return an Error
 // object if the validation fails. Don't `console.warn` or throw, as this
 // won't work inside `oneOfType`.
 customProp: function(props, propName, componentName) {
   if (!/matchme/.test(props[propName])) {
      return new Error(
        'Invalid prop `' + propName + '` supplied to' +
        ' ` ' + componentName + '`. Validation failed.'
     );
    }
 },
 // You can also supply a custom validator to `arrayOf` and `objectOf`.
 // It should return an Error object if the validation fails. The validator
 // will be called for each key in the array or object. The first two
 // arguments of the validator are the array or object itself, and the
 // current item's key.
 customArrayProp: PropTypes.arrayOf(function(propValue, key, componentName, location,
propFullName) {
   if (!/matchme/.test(propValue[key])) {
     return new Error(
        'Invalid prop `' + propFullName + '` supplied to' +
        ' `' + componentName + '`. Validation failed.'
     );
    }
 })
};
```

## **Requiring Single Child**



With PropTypes.element you can specify that only a single child can be passed to a component as children.

### **Default Prop Values**

You can define default values for your props by assigning to the special defaultProps property:



If you are using a Babel transform like <u>transform-class-properties</u>, you can also declare defaultProps as static property within a React component class. This syntax has not yet been finalized though and will require a compilation step to work within a browser. For more information, see the class fields proposal.

```
class Greeting extends React.Component {
  static defaultProps = {
    name: 'stranger'
  }

  render() {
    return (
        <div>Hello, {this.props.name}</div>
    )
  }
}
```

The defaultProps will be used to ensure that this.props.name will have a value if it was not specified by the parent component. The propTypes typechecking happens after defaultProps are resolved, so typechecking will also apply to the defaultProps.

DOCS	CHANNELS

Installation

Main Concepts

**Advanced Guides** 

**API** Reference

Contributing

FAO

GitHub ぱ

Stack Overflow &

Discussion Forum **I** 

Reactiflux Chat 2

DEV Community 더

Facebook 🗗

Twitter ☑



COMMUNITY	MORE
Community Resources	Tutorial
Tools	Blog
	Acknowledgements
	React Native 🗗

Copyright © 2018 Facebook Inc.

