



The University of New Mexico

Hierarchical Modeling I

Ed Angel

Professor Emeritus of Computer Science,
University of New Mexico



Objectives


- Examine the limitations of linear modeling
 - Symbols and instances
- Introduce hierarchical models
 - Articulated models
 - Robots
- Introduce Tree and DAG models



Instance Transformation

The University of New Mexico

- Start with a prototype object (a *symbol*)
- Each appearance of the object in the model is an *instance*
 - Must scale, orient, position
 - Defines instance transformation





Symbol-Instance Table


Can store a model by assigning a number to each symbol and storing the parameters for the instance transformation

Symbol	Scale	Rotate	Translate
1	$s_{x'}, s_{y'}, s_z$	$\theta_{x'}, \theta_{y'}, \theta_z$	$d_{x'}, d_{y'}, d_z$
2			
3			
1			
1			
.			
.			



Relationships in Car Model

- Symbol-instance table does not show relationships between parts of model
- Consider model of car
 - Chassis + 4 identical wheels
 - Two symbols



- Rate of forward motion determined by rotational speed of wheels



Structure Through Function Calls


```
car(speed)
{
    chassis()
    wheel(right_front);
    wheel(left_front);
    wheel(right_rear);
    wheel(left_rear);
}
```

- Fails to show relationships well
- Look at problem using a graph



Graphs


- Set of *nodes* and *edges (links)*
- Edge connects a pair of nodes
 - Directed or undirected
- *Cycle*: directed path that is a loop






Tree

- Graph in which each node (except the root) has exactly one parent node
 - May have multiple children
 - Leaf or terminal node: no children






Tree Model of Car





DAG Model

- If we use the fact that all the wheels are identical, we get a *directed acyclic graph*
 - Not much different than dealing with a tree






Modeling with Trees

- Must decide what information to place in nodes and what to put in edges
- Nodes
 - What to draw
 - Pointers to children
- Edges
 - May have information on incremental changes to transformation matrices (can also store in nodes)






The University of New Mexico

Robot Arm



robot arm




parts in their own
coordinate systems



Articulated Models

- Robot arm is an example of an *articulated model*
 - Parts connected at joints
 - Can specify state of model by giving all joint angles





Relationships in Robot Arm

- Base rotates independently
 - Single angle determines position
- Lower arm attached to base
 - Its position depends on rotation of base
 - Must also translate relative to base and rotate about connecting joint
- Upper arm attached to lower arm
 - Its position depends on both base and lower arm
 - Must translate relative to lower arm and rotate about joint connecting to lower arm



Required Matrices

- Rotation of base: \mathbf{R}_b
 - Apply $\mathbf{M} = \mathbf{R}_b$ to base
- Translate lower arm relative to base: \mathbf{T}_{lu}
- Rotate lower arm around joint: \mathbf{R}_{lu}
 - Apply $\mathbf{M} = \mathbf{R}_b \mathbf{T}_{lu} \mathbf{R}_{lu}$ to lower arm
- Translate upper arm relative to upper arm: \mathbf{T}_{uu}
- Rotate upper arm around joint: \mathbf{R}_{uu}
 - Apply $\mathbf{M} = \mathbf{R}_b \mathbf{T}_{lu} \mathbf{R}_{lu} \mathbf{T}_{uu} \mathbf{R}_{uu}$ to upper arm




OpenGL Code for Robot

```
mat4 ctm;  
robot_arm()  
{  
    ctm = RotateY(theta) ;  
    base() ;  
    ctm *= Translate(0.0, h1, 0.0) ;  
    ctm *= RotateZ(phi) ;  
    lower_arm() ;  
    ctm *= Translate(0.0, h2, 0.0) ;  
    ctm *= RotateZ(psi) ;  
    upper_arm() ;  
}
```




Tree Model of Robot


- Note code shows relationships between parts of model
 - Can change “look” of parts easily without altering relationships
- Simple example of tree model
- Want a general node structure for nodes





Possible Node Structure

The University of New Mexico



matrix relating node to parent



Generalizations

- Need to deal with multiple children
 - How do we represent a more general tree?
 - How do we traverse such a data structure?
- Animation
 - How to use dynamically?
 - Can we create and delete nodes during execution?