



The University of New Mexico

Representation

Ed Angel

Professor Emeritus of Computer Science,
University of New Mexico



Objectives

- Introduce concepts such as dimension and basis
- Introduce coordinate systems for representing vectors spaces and frames for representing affine spaces
- Discuss change of frames and bases
- Introduce homogeneous coordinates



Linear Independence

- A set of vectors v_1, v_2, \dots, v_n is *linearly independent* if

$$\alpha_1 v_1 + \alpha_2 v_2 + \dots + \alpha_n v_n = 0 \text{ iff } \alpha_1 = \alpha_2 = \dots = 0$$

- If a set of vectors is linearly independent, we cannot represent one in terms of the others
- If a set of vectors is linearly dependent, at least one can be written in terms of the others



Dimension

- In a vector space, the maximum number of linearly independent vectors is fixed and is called the *dimension* of the space
- In an n -dimensional space, any set of n linearly independent vectors form a *basis* for the space
- Given a basis v_1, v_2, \dots, v_n , any vector v can be written as

$$v = \alpha_1 v_1 + \alpha_2 v_2 + \dots + \alpha_n v_n$$

where the $\{\alpha_i\}$ are unique



Representation

- Until now we have been able to work with geometric entities without using any frame of reference, such as a coordinate system
- Need a frame of reference to relate points and objects to our physical world.
 - For example, where is a point? Can't answer without a reference system
 - World coordinates
 - Camera coordinates



Coordinate Systems

- Consider a basis v_1, v_2, \dots, v_n
- A vector is written $v = \alpha_1 v_1 + \alpha_2 v_2 + \dots + \alpha_n v_n$
- The list of scalars $\{\alpha_1, \alpha_2, \dots, \alpha_n\}$ is the *representation* of v with respect to the given basis
- We can write the representation as a row or column array of scalars

$$\mathbf{a} = [\alpha_1 \quad \alpha_2 \quad \dots \quad \alpha_n]^T = \begin{bmatrix} \alpha_1 \\ \alpha_2 \\ \vdots \\ \alpha_n \end{bmatrix}$$



Example



-
- $\mathbf{v} = 2\mathbf{v}_1 + 3\mathbf{v}_2 - 4\mathbf{v}_3$
 - $\mathbf{a} = [2 \ 3 \ -4]^T$
 - Note that this representation is with respect to a particular basis
 - For example, in OpenGL we start by representing vectors using the object basis but later the system needs a representation in terms of the camera or eye basis



The University of New Mexico

Coordinate Systems

- Which is correct?




- Both are because vectors have no fixed location



Frames

- A coordinate system is insufficient to represent points
- If we work in an affine space we can add a single point, the *origin*, to the basis vectors to form a *frame*





Representation in a Frame

- Frame determined by (P_0, v_1, v_2, v_3)
- Within this frame, every vector can be written as

$$v = \alpha_1 v_1 + \alpha_2 v_2 + \dots + \alpha_n v_n$$

- Every point can be written as

$$P = P_0 + \beta_1 v_1 + \beta_2 v_2 + \dots + \beta_n v_n$$

Confusing Points and Vectors

Consider the point and the vector

$$P = P_0 + \beta_1 v_1 + \beta_2 v_2 + \dots + \beta_n v_n$$

$$v = \alpha_1 v_1 + \alpha_2 v_2 + \dots + \alpha_n v_n$$


They appear to have the similar representations

$$\mathbf{p} = [\beta_1 \ \beta_2 \ \beta_3] \quad \mathbf{v} = [\alpha_1 \ \alpha_2 \ \alpha_3]$$

which confuses the point with the vector

A vector has no position

Vector can be placed anywhere



point: fixed



A Single Representation

If we define $0 \bullet P = \mathbf{0}$ and $1 \bullet P = P$ then we can write

$$\mathbf{v} = \alpha_1 v_1 + \alpha_2 v_2 + \alpha_3 v_3 = [\alpha_1 \ \alpha_2 \ \alpha_3 \ 0] [v_1 \ v_2 \ v_3 \ P_0]^T$$

$$P = P_0 + \beta_1 v_1 + \beta_2 v_2 + \beta_3 v_3 = [\beta_1 \ \beta_2 \ \beta_3 \ 1] [v_1 \ v_2 \ v_3 \ P_0]^T$$

Thus we obtain the four-dimensional
homogeneous coordinate representation

$$\mathbf{v} = [\alpha_1 \ \alpha_2 \ \alpha_3 \ 0]^T$$

$$\mathbf{p} = [\beta_1 \ \beta_2 \ \beta_3 \ 1]^T$$



Homogeneous Coordinates

The homogeneous coordinates form for a three dimensional point $[x \ y \ z]$ is given as

$$\mathbf{p} = [x' \ y' \ z' \ w]^T = [wx \ wy \ wz \ w]^T$$

We return to a three dimensional point (for $w \neq 0$) by

$$x \leftarrow x'/w$$

$$y \leftarrow y'/w$$

$$z \leftarrow z'/w$$

If $w=0$, the representation is that of a vector

Note that homogeneous coordinates replaces points in three dimensions by lines through the origin in four dimensions

For $w=1$, the representation of a point is $[x \ y \ z \ 1]$



Homogeneous Coordinates and Computer Graphics

- Homogeneous coordinates are key to all computer graphics systems
 - All standard transformations (rotation, translation, scaling) can be implemented with matrix multiplications using 4×4 matrices
 - Hardware pipeline works with 4 dimensional representations
 - For orthographic viewing, we can maintain $w=0$ for vectors and $w=1$ for points
 - For perspective we need a *perspective division*



Change of Coordinate Systems

- Consider two representations of a the same vector with respect to two different bases. The representations are

$$\mathbf{a} = [\alpha_1 \ \alpha_2 \ \alpha_3]$$

$$\mathbf{b} = [\beta_1 \ \beta_2 \ \beta_3]$$

where

$$\begin{aligned} \mathbf{v} &= \alpha_1 \mathbf{v}_1 + \alpha_2 \mathbf{v}_2 + \alpha_3 \mathbf{v}_3 = [\alpha_1 \ \alpha_2 \ \alpha_3] [\mathbf{v}_1 \ \mathbf{v}_2 \ \mathbf{v}_3]^T \\ &= \beta_1 \mathbf{u}_1 + \beta_2 \mathbf{u}_2 + \beta_3 \mathbf{u}_3 = [\beta_1 \ \beta_2 \ \beta_3] [\mathbf{u}_1 \ \mathbf{u}_2 \ \mathbf{u}_3]^T \end{aligned}$$


Representing second basis in terms of first

Each of the basis vectors, u_1, u_2, u_3 , are vectors that can be represented in terms of the first basis

$$u_1 = \gamma_{11}v_1 + \gamma_{12}v_2 + \gamma_{13}v_3$$

$$u_2 = \gamma_{21}v_1 + \gamma_{22}v_2 + \gamma_{23}v_3$$

$$u_3 = \gamma_{31}v_1 + \gamma_{32}v_2 + \gamma_{33}v_3$$





Matrix Form

The coefficients define a 3 x 3 matrix

$$\mathbf{M} = \begin{bmatrix} \gamma_{11} & \gamma_{12} & \gamma_{13} \\ \gamma_{21} & \gamma_{22} & \gamma_{23} \\ \gamma_{31} & \gamma_{32} & \gamma_{33} \end{bmatrix}$$

and the bases can be related by

$$\mathbf{a} = \mathbf{M}^T \mathbf{b}$$

see text for numerical examples




Change of Frames

- We can apply a similar process in homogeneous coordinates to the representations of both points and vectors

Consider two frames:

(P_0, v_1, v_2, v_3)

(Q_0, u_1, u_2, u_3)



- Any point or vector can be represented in either frame
- We can represent Q_0, u_1, u_2, u_3 in terms of P_0, v_1, v_2, v_3

Representing One Frame in Terms of the Other

Extending what we did with change of bases

$$u_1 = \gamma_{11}v_1 + \gamma_{12}v_2 + \gamma_{13}v_3$$

$$u_2 = \gamma_{21}v_1 + \gamma_{22}v_2 + \gamma_{23}v_3$$

$$u_3 = \gamma_{31}v_1 + \gamma_{32}v_2 + \gamma_{33}v_3$$

$$Q_0 = \gamma_{41}v_1 + \gamma_{42}v_2 + \gamma_{43}v_3 + \gamma_{44}P_0$$

defining a 4 x 4 matrix

$$\mathbf{M} = \begin{bmatrix} \gamma_{11} & \gamma_{12} & \gamma_{13} & 0 \\ \gamma_{21} & \gamma_{22} & \gamma_{23} & 0 \\ \gamma_{31} & \gamma_{32} & \gamma_{33} & 0 \\ \gamma_{41} & \gamma_{42} & \gamma_{43} & 1 \end{bmatrix}$$



Working with Representations

Within the two frames any point or vector has a representation of the same form

$\mathbf{a} = [\alpha_1 \ \alpha_2 \ \alpha_3 \ \alpha_4]$ in the first frame

$\mathbf{b} = [\beta_1 \ \beta_2 \ \beta_3 \ \beta_4]$ in the second frame

where $\alpha_4 = \beta_4 = 1$ for points and $\alpha_4 = \beta_4 = 0$ for vectors and

$$\mathbf{a} = \mathbf{M}^T \mathbf{b}$$

The matrix \mathbf{M} is 4 x 4 and specifies an affine transformation in homogeneous coordinates



Affine Transformations

- Every linear transformation is equivalent to a change in frames
- Every affine transformation preserves lines
- However, an affine transformation has only 12 *degrees of freedom* because 4 of the elements in the matrix are fixed and are a subset of all possible 4 x 4 linear transformations



The World and Camera Frames


- When we work with representations, we work with n-tuples or arrays of scalars
- Changes in frame are then defined by 4 x 4 matrices
- In OpenGL, the base frame that we start with is the world frame
- Eventually we represent entities in the camera frame by changing the world representation using the model-view matrix
- Initially these frames are the same ($\mathbf{M}=\mathbf{I}$)




Moving the Camera

If objects are on both sides of $z=0$, we must move camera frame

$$\mathbf{M} = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & -d \\ 0 & 0 & 0 & 1 \end{bmatrix}$$



(a)



(b)