



IOS STATIC ANALYSIS REPORT




🍏 MeetWay (1.1.3)

File Name:	MeetWay.ipa
Identifier:	AIVAR022-2025-1.0
Scan Date:	April 9, 2026, 3:55 p.m.

App Security Score:

40/100 (MEDIUM RISK)

Grade:



 FINDINGS SEVERITY

 HIGH	 MEDIUM	 INFO	 SECURE	 HOTSPOT
3	4	2	1	2

 FILE INFORMATION

File Name: MeetWay.ipa
Size: 45.14MB
MD5: 9c662e0a1be9a6d52db9474b05861804
SHA1: 899633efbe876a273655d54536af1c3ef0839ba6

SHA256: 24be92425c56a6bb87986e23bc6c8fe2fe5bf0a4dbe748d2f4f4002985dff89

i APP INFORMATION

App Name: MeetWay
App Type: Objective C
Identifier: AIVARO22-2025-1.0
SDK Name: iphoneos18.5
Version: 1.1.3
Build: 1
Platform Version: 18.5
Min OS Version: 17.6
Supported Platforms: iPhoneOS,

Ad BINARY INFORMATION

Arch: ARM64
Sub Arch: CPU_SUBTYPE_ARM64_ALL
Bit: 64-bit
Endian: <

#CUSTOM URL SCHEMES

URL NAME	SCHEMES
YandexLoginSDK	yx547697fe6e9d46ea9a7e538922d1425d

≡ APPLICATION PERMISSIONS

PERMISSIONS	STATUS	INFO	REASON IN MANIFEST
NSCameraUsageDescription	dangerous	Access the Camera.	Приложение запрашивает доступ к камере для создания фотографий профиля и мест
NSContactsUsageDescription	dangerous	Access Contacts.	Приложение запрашивает доступ к контактам для поиска друзей в приложении
NSLocationWhenInUseUsageDescription	dangerous	Access location information when app is in the foreground.	Приложение использует геолокацию для отметки посещенных мест на карте
NSMicrophoneUsageDescription	dangerous	Access microphone.	Приложение запрашивает доступ к микрофону для записи голосовых сообщений
NSPhotoLibraryUsageDescription	dangerous	Access the user's photo library.	Приложение сохраняет выбранные фото в ваш профиль

APP TRANSPORT SECURITY (ATS)

HIGH: 2 | WARNING: 1 | INFO: 2 | SECURE: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	App Transport Security AllowsArbitraryLoads is allowed	high	App Transport Security restrictions are disabled for all network connections. Disabling ATS means that unsecured HTTP connections are allowed. HTTPS connections are also allowed, and are still subject to default server trust evaluation. However, extended security checks like requiring a minimum Transport Layer Security (TLS) protocol version—are disabled. This setting is not applicable to domains listed in NSExceptionDomains.
2	NSExceptionDomains	info	storage.yandexcloud.net
3	Insecure communication to storage.yandexcloud.net is allowed	high	NSExceptionAllowsInsecureHTTPLoads allows insecure HTTP loads to storage.yandexcloud.net, or to be able to loosen the server trust evaluation requirements for HTTPS connections to the domain.
4	NSIncludesSubdomains set to TRUE for storage.yandexcloud.net	info	NSIncludesSubdomains applies the ATS exceptions for the given domain to all subdomains as well. For example, the ATS exceptions in the domain exception dictionary apply to storage.yandexcloud.net, as well as math.storage.yandexcloud.net, history.storage.yandexcloud.net, and so on. Otherwise, if the value is NO, the exceptions apply only to storage.yandexcloud.net.
5	NSRequiresCertificateTransparency set to NO for storage.yandexcloud.net	warning	Certificate Transparency (CT) is a protocol that ATS can use to identify mistakenly or maliciously issued X.509 certificates. Set the value for the NSRequiresCertificateTransparency key to YES to require that for a given domain, server certificates are supported by valid, signed CT timestamps from at least two CT logs trusted by Apple. This key is optional. The default value is NO.

</> IPA BINARY CODE ANALYSIS

HIGH: 0 | WARNING: 1 | INFO: 0 | SECURE: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	DESCRIPTION
1	Binary makes use of insecure API(s)	warning	CWE: CWE-676: Use of Potentially Dangerous Function OWASP Top 10: M7: Client Code Quality OWASP MASVS: MSTG-CODE-8	The binary may contain the following insecure API(s) _memcpy , _printf , _strlen

🔒 IPA BINARY ANALYSIS

PROTECTION	STATUS	SEVERITY	DESCRIPTION
NX	True	info	The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.
PIE	True	info	The binary is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.
STACK CANARY	True	info	This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.

PROTECTION	STATUS	SEVERITY	DESCRIPTION
ARC	False	high	The binary is not compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and protects from memory corruption vulnerabilities. Use compiler option -fobjc-arc to enable ARC or set Objective-C Automatic Reference Counting to YES in project configuration.
RPATH	True	warning	The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.
CODE SIGNATURE	True	info	This binary has a code signature.
ENCRYPTED	False	warning	This binary is not encrypted.
SYMBOLS STRIPPED	False	warning	Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

 DYNAMIC LIBRARY & FRAMEWORK BINARY ANALYSIS

NO	DYLIB/Framework	NX	Stack Canary	ARC	RPATH	Code Signature	Encrypted	Symbols Stripped
----	-----------------	----	--------------	-----	-------	----------------	-----------	------------------

NO	DYLIB/Framework	NX	Stack Canary	ARC	RPATH	Code Signature	Encrypted	Symbols Stripped
1	MeetWay.app/__preview.dylib	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries.	False high The binary is not compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and protects from memory corruption vulnerabilities. Use compiler option -fobjc-arc to enable ARC or set Objective-C Automatic Reference Counting to YES in project configuration.	False info The binary does not have Runpath Search Path (@rpath) set.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	Stack Canary	ARC	RPATH	Code Signature	Encrypted	Symbols Stripped
2	MeetWay.app/MeetWay.debug.dylib	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	True info The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
1	Payload/MeetWay.app/Frameworks/absl.framework/absl	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	False high The binary is not compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and protects from memory corruption vulnerabilities. Use compiler option -fobjc-arc to enable ARC or set Objective-C Automatic Reference Counting to YES in project configuration.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
2	Payload/MeetWay.app/Frameworks/grpcpp.framework/grpcpp	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	False high The binary is not compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and protects from memory corruption vulnerabilities. Use compiler option -fobjc-arc to enable ARC or set Objective-C Automatic Reference Counting to YES in project configuration.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
3	Payload/MeetWay.app/Frameworks/FirebaseCore.framework/FirebaseCore	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	True info The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
4	Payload/MeetWay.app/Frameworks/leveldb.framework/leveldb	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	False high The binary is not compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and protects from memory corruption vulnerabilities. Use compiler option -fobjc-arc to enable ARC or set Objective-C Automatic Reference Counting to YES in project configuration.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
5	Payload/MeetWay.app/Frameworks/FBLPromises.framework/FBLPromises	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	True info The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
6	Payload/MeetWay.app/Frameworks/nanopb.framework/nanopb	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	False high The binary is not compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and protects from memory corruption vulnerabilities. Use compiler option -fobjc-arc to enable ARC or set Objective-C Automatic Reference Counting to YES in project configuration.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
7	Payload/MeetWay.app/Frameworks/FirebaseAuthInterop.framework/FirebaseAuthInterop	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries.	False high The binary is not compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and protects from memory corruption vulnerabilities. Use compiler option -fobjc-arc to enable ARC or set Objective-C Automatic Reference Counting to YES in project configuration.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
8	Payload/MeetWay.app/Frameworks/openssl_grpc.framework/openssl_grpc	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	False high The binary is not compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and protects from memory corruption vulnerabilities. Use compiler option -fobjc-arc to enable ARC or set Objective-C Automatic Reference Counting to YES in project configuration.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
9	Payload/MeetWay.app/Frameworks/FirebaseMessaging.framework/FirebaseMessaging	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	True info The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
10	Payload/MeetWay.app/Frameworks/RecaptchaInterop.framework/RecaptchaInterop	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries.	False high The binary is not compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and protects from memory corruption vulnerabilities. Use compiler option -fobjc-arc to enable ARC or set Objective-C Automatic Reference Counting to YES in project configuration.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
11	Payload/MeetWay.app/Frameworks/AWSS3.framework/AWSS3	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	True info The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
12	Payload/MeetWay.app/Frameworks/AWSCore.framework/AWSCore	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	True info The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
13	Payload/MeetWay.app/Frameworks/grpc.framework/grpc	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	False high The binary is not compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and protects from memory corruption vulnerabilities. Use compiler option -fobjc-arc to enable ARC or set Objective-C Automatic Reference Counting to YES in project configuration.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
14	Payload/MeetWay.app/Frameworks/FirebaseInstallations.framework/FirebaseInstallations	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	True info The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
15	Payload/MeetWay.app/Frameworks/FirebaseSharedSwift.framework/FirebaseSharedSwift	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option - fstack-protector-all to enable stack canaries.	True info The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option - rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
16	Payload/MeetWay.app/Frameworks/FirebaseAppCheckInterop.framework/FirebaseAppCheckInterop	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries.	False high The binary is not compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and protects from memory corruption vulnerabilities. Use compiler option -fobjc-arc to enable ARC or set Objective-C Automatic Reference Counting to YES in project configuration.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
17	Payload/MeetWay.app/Frameworks/GoogleUtilities.framework/GoogleUtilities	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	True info The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
18	Payload/MeetWay.app/Frameworks/FirebaseAuth.framework/FirebaseAuth	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	True info The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
19	Payload/MeetWay.app/Frameworks/FirebaseFirestoreInternal.framework/FirebaseFirestoreInternal	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	True info The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
20	Payload/MeetWay.app/Frameworks/FirebaseFirestore.framework/FirebaseFirestore	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	True info The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
21	Payload/MeetWay.app/Frameworks/FirebaseCoreInternal.framework/FirebaseCoreInternal	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	True info The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
22	Payload/MeetWay.app/Frameworks/GTMSessionFetcher.framework/GTMSessionFetcher	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	True info The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
23	Payload/MeetWay.app/Frameworks/YandexLoginSDK.framework/YandexLoginSDK	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	True info The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
24	Payload/MeetWay.app/Frameworks/GoogleDataTransport.framework/GoogleDataTransport	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	True info The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

NO	DYLIB/Framework	NX	STACK CANARY	ARC	RPATH	CODE SIGNATURE	ENCRYPTED	SYMBOLS STRIPPED
25	Payload/MeetWay.app/Frameworks/FirebaseCoreExtension.framework/FirebaseCoreExtension	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries.	False high The binary is not compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and protects from memory corruption vulnerabilities. Use compiler option -fobjc-arc to enable ARC or set Objective-C Automatic Reference Counting to YES in project configuration.	True warning The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.	True info This binary has a code signature.	False warning This binary is not encrypted.	False warning Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.

</> CODE ANALYSIS

NO	ISSUE	SEVERITY	STANDARDS	FILES
----	-------	----------	-----------	-------

! OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION
--------	----------------

 DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
sts.cn-north-1.amazonaws.com	ok	No Geolocation information available.
www.google.com	ok	IP: 142.251.151.119 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
fcmtoken.googleapis.com	ok	IP: 142.251.29.95 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
sts.us-gov-west-1.amazonaws.com	ok	IP: 52.46.224.244 Country: United States of America Region: Washington City: Seattle Latitude: 47.627499 Longitude: -122.346199 View: Google Map
example.invalid	ok	No Geolocation information available.
www.googleapis.com	ok	IP: 142.251.1.95 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
device-provisioning.googleapis.com	ok	IP: 142.251.1.95 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
docs.aws.amazon.com	ok	IP: 13.33.235.6 Country: Spain Region: Madrid, Comunidad de City: Madrid Latitude: 40.416500 Longitude: -3.702560 View: Google Map
www.amazon.com	ok	IP: 23.32.25.222 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
mozilla.org	ok	IP: 35.190.14.201 Country: United States of America Region: Missouri City: Kansas City Latitude: 39.099731 Longitude: -94.578568 View: Google Map
ocsp.apple.com	ok	IP: 17.253.39.133 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
www.catcert.net	ok	IP: 13.33.235.21 Country: Spain Region: Madrid, Comunidad de City: Madrid Latitude: 40.416500 Longitude: -3.702560 View: Google Map
dummyapiverylong-dummy.google.com	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
empretradingsupport.tilda.ws	ok	IP: 178.248.234.146 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
www.sandbox.googleapis.com	ok	IP: 192.178.223.129 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
functions.yandexcloud.net	ok	IP: 84.201.162.181 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
www.entrust.net	ok	IP: 216.117.57.240 Country: United States of America Region: Texas City: Dallas Latitude: 32.933300 Longitude: -96.783501 View: Google Map
www.digits.com	ok	IP: 34.95.92.107 Country: United States of America Region: Missouri City: Kansas City Latitude: 39.099731 Longitude: -94.578568 View: Google Map
crl.apple.com	ok	IP: 17.253.39.134 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map

DOMAIN	STATUS	GEOLOCATION
firebaseinstallations.googleapis.com	ok	IP: 209.85.233.95 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
firebase.google.com	ok	IP: 173.194.73.102 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.digicert.com	ok	IP: 45.60.129.229 Country: United Kingdom of Great Britain and Northern Ireland Region: England City: London Latitude: 51.508530 Longitude: -0.125740 View: Google Map
certs.apple.com	ok	IP: 17.253.39.133 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
login.yandex.ru	ok	IP: 87.250.254.120 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
console.firebase.google.com	ok	IP: 64.233.165.139 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.w3.org	ok	IP: 8.47.69.6 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
www.apple.com	ok	IP: 184.24.145.53 Country: United States of America Region: Georgia City: Atlanta Latitude: 33.749001 Longitude: -84.387978 View: Google Map
iid.googleapis.com	ok	IP: 142.250.140.95 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
cns.api.ilb.cloud.yandex.net	ok	No Geolocation information available.
cloud.google.com	ok	IP: 142.250.117.113 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
sts.amazonaws.com	ok	IP: 209.54.180.124 Country: United States of America Region: Virginia City: Ashburn Latitude: 39.043720 Longitude: -77.487488 View: Google Map

DOMAIN	STATUS	GEOLOCATION
storage.yandexcloud.net	ok	IP: 213.180.193.243 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
www.xrampsecurity.com	ok	IP: 3.216.249.84 Country: United States of America Region: Virginia City: Ashburn Latitude: 39.043720 Longitude: -77.487488 View: Google Map

EMAILS

EMAIL	FILE
z@github.com	Payload/MeetWay.app/Frameworks/grpc.framework/grpc

HARDCODED SECRETS

POSSIBLE SECRETS
API_KEY : AlzaSyBYF96ObWXyrvpYllliH4J07hgcNxKzjEM

SCAN LOGS

Timestamp	Event	Error
2026-04-09 15:55:12	iOS Binary (IPA) Analysis Started	OK
2026-04-09 15:55:12	Generating Hashes	OK

2026-04-09 15:55:12	Extracting IPA	OK
2026-04-09 15:55:12	Unzipping	OK
2026-04-09 15:55:13	iOS File Analysis and Normalization	OK
2026-04-09 15:55:13	iOS Info.plist Analysis Started	OK
2026-04-09 15:55:13	Finding Info.plist in iOS Binary	OK
2026-04-09 15:55:13	Fetching Details from App Store: AIVARO22-2025-1.0	OK
2026-04-09 15:55:13	Searching for secrets in plist files	OK
2026-04-09 15:55:13	Starting Binary Analysis	OK
2026-04-09 15:55:13	Dumping Classes from the binary	OK
2026-04-09 15:55:13	Running jtool against the binary for dumping classes	OK
2026-04-09 15:55:13	Library Binary Analysis Started	OK
2026-04-09 15:55:13	Analyzing Payload/MeetWay.app/__preview.dylib	OK
2026-04-09 15:55:13	Analyzing Payload/MeetWay.app/MeetWay.debug.dylib	OK
2026-04-09 15:55:14	Framework Binary Analysis Started	OK
2026-04-09 15:55:14	Analyzing Payload/MeetWay.app/Frameworks/absl.framework/absl	OK

2026-04-09 15:55:14	Analyzing Payload/MeetWay.app/Frameworks/grpcpp.framework/grpcpp	OK
2026-04-09 15:55:14	Analyzing Payload/MeetWay.app/Frameworks/FirebaseCore.framework/FirebaseCore	OK
2026-04-09 15:55:15	Analyzing Payload/MeetWay.app/Frameworks/leveldb.framework/leveldb	OK
2026-04-09 15:55:15	Analyzing Payload/MeetWay.app/Frameworks/FBLPromises.framework/FBLPromises	OK
2026-04-09 15:55:15	Analyzing Payload/MeetWay.app/Frameworks/nanopb.framework/nanopb	OK
2026-04-09 15:55:15	Analyzing Payload/MeetWay.app/Frameworks/FirebaseAuthInterop.framework/FirebaseAuthInterop	OK
2026-04-09 15:55:15	Analyzing Payload/MeetWay.app/Frameworks/openssl_grpc.framework/openssl_grpc	OK
2026-04-09 15:55:15	Analyzing Payload/MeetWay.app/Frameworks/FirebaseMessaging.framework/FirebaseMessaging	OK
2026-04-09 15:55:15	Analyzing Payload/MeetWay.app/Frameworks/RecaptchaInterop.framework/RecaptchaInterop	OK
2026-04-09 15:55:15	Analyzing Payload/MeetWay.app/Frameworks/AWSS3.framework/AWSS3	OK
2026-04-09 15:55:15	Analyzing Payload/MeetWay.app/Frameworks/AWSCore.framework/AWSCore	OK
2026-04-09 15:55:15	Analyzing Payload/MeetWay.app/Frameworks/grpc.framework/grpc	OK
2026-04-09 15:55:16	Analyzing Payload/MeetWay.app/Frameworks/FirebaseInstallations.framework/FirebaseInstallations	OK
2026-04-09 15:55:16	Analyzing Payload/MeetWay.app/Frameworks/FirebaseSharedSwift.framework/FirebaseSharedSwift	OK
2026-04-09 15:55:17	Analyzing Payload/MeetWay.app/Frameworks/FirebaseAppCheckInterop.framework/FirebaseAppCheckInterop	OK

2026-04-09 15:55:17	Analyzing Payload/MeetWay.app/Frameworks/GoogleUtilities.framework/GoogleUtilities	OK
2026-04-09 15:55:17	Analyzing Payload/MeetWay.app/Frameworks/FirebaseAuth.framework/FirebaseAuth	OK
2026-04-09 15:55:17	Analyzing Payload/MeetWay.app/Frameworks/FirebaseFirestoreInternal.framework/FirebaseFirestoreInternal	OK
2026-04-09 15:55:17	Analyzing Payload/MeetWay.app/Frameworks/FirebaseFirestore.framework/FirebaseFirestore	OK
2026-04-09 15:55:18	Analyzing Payload/MeetWay.app/Frameworks/FirebaseCoreInternal.framework/FirebaseCoreInternal	OK
2026-04-09 15:55:18	Analyzing Payload/MeetWay.app/Frameworks/GTMSessionFetcher.framework/GTMSessionFetcher	OK
2026-04-09 15:55:18	Analyzing Payload/MeetWay.app/Frameworks/YandexLoginSDK.framework/YandexLoginSDK	OK
2026-04-09 15:55:18	Analyzing Payload/MeetWay.app/Frameworks/GoogleDataTransport.framework/GoogleDataTransport	OK
2026-04-09 15:55:18	Analyzing Payload/MeetWay.app/Frameworks/FirebaseCoreExtension.framework/FirebaseCoreExtension	OK
2026-04-09 15:55:18	Extracting String Metadata	OK
2026-04-09 15:55:18	Extracting URL and Email from IPA	OK
2026-04-09 15:55:46	Performing Malware check on extracted domains	OK
2026-04-09 15:55:56	Fetching IPA icon path	OK
2026-04-09 15:55:57	Detecting Trackers from Domains	OK
2026-04-09 15:55:57	Saving to Database	OK

Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | [Ajin Abraham](#) | [OpenSecurity](#).