
EVEGLYPHDESIGN · HAWKINS TWIN PLATFORM

Warranty GENE — Schema v1

VIN rich-target row, coverage math, and sample fixtures

The row that answers, per VIN, per day, whether the truck belongs on Tim's booking calendar this week.

What this schema is

A single JSON row per VIN, produced daily by the twin, consumed by two surfaces:

- **The executive control surface** — the fourth cohort tile beside the three existing TELUS-style tiles, ordered by `score.total` descending.
- **The outbound-booking worklist** — filtered to `compliance.clean == true` and `booking_urgency ∈ {inbound-tonight, inbound-this-week, in-region}`, handed to the counter for outreach.

Any row failing `compliance.clean` routes to the **review lane** instead of the booking lane. A human decides what to do with it.

What this schema is not

- Not a claim submission payload. PRWS remains authoritative; the GENE flags candidates, humans file claims.
- Not a copy of customer data. `owner.customer_id` is the CDK master id only; the payload — names, phones, VIN histories — stays in Hawkins-owned Azure Postgres.
- Not a source of coverage truth. SIR and SmartLINQ Service Management remain the eligibility source of record; the GENE reads them and encodes what it reads with `source_provenance` intact.

Files

- `rich-target.schema.json` — JSON Schema Draft 2020-12
- `../samples/rich-targets.sample.json` — 7 synthetic VINs across Class 8 diesel, Class 8 MX, Class 6/7, and battery electric
- `../samples/rich-targets.worklist.json` — compact projection for the fourth-cohort tile
- `../scoring.md` — deterministic 0–100 score formula
- `../scripts/build_samples.py` — reproduces the samples deterministically
- `../scripts/validate.py` — validates every sample against the schema

The row at a glance

record_id	sha1(vin + as_of_date)	idempotent per day
vin	17-char PACCAR-validated	
as_of	ISO-8601 UTC	
chassis	{ model, class, series[], in_service_date, vocational_use }	
usage	{ odometer_km, engine_hours?, as_of, source }	
owner	{ customer_id, customer_type, fleet_id?, home_rooftop }	
coverage	{ <ten buckets> } – only applicable ones present each: applies, months_remaining, distance_remaining_km, hours_remaining?, expiry_reason	
open_jobs[]	{ job_id, authority, type, component, ata_code?, coverage_bucket, estimated_srt_hours, parts_on_hand?, customer_pay_at_risk_cad?, status, source_bulletin_url? }	
score	{ margin_estimate_cad, time_to_expiry_days, booking_urgency, total }	
compliance	{ clean, flags{5 booleans} }	
telemetry?	{ last_ping, in_hawkins_region, projected_overnight_region, geofence_confidence }	
source_provenance[]	{ source, captured_at, note? }	

Coverage buckets

Modelled directly against the 2025.4 Warranty Quick Reference Guide, Coverage Time & Exclusions table:

Key	Applies to
base_emissions_carb	CARB-registered chassis
base_emissions_epa_eccc	EPA/ECCC-registered chassis
standard_vehicle	All chassis
standard_mx_engine	MX-equipped Class 8
engine_major_components	MX-equipped Class 8
vehicle_major_components	All chassis (definition varies by class)
severe_service	Chassis in a defined severe-service vocation
paccar_alternator_starter	Chassis with PACCAR-branded charging set

Key	Applies to
paccar_front_axles	Chassis with PACCAR-branded front axle
non_paccar_front_axles	Chassis with non-PACCAR front axle
bev_ess	Battery-electric chassis (energy storage)

Buckets that do not apply to a given chassis are simply omitted from the row.

Authority hierarchy for open jobs

Ordered from highest authority to lowest, matching the Warranty Procedure Manual v2026.7:

- 1. Federal Safety Recall
- 2. Field Repair Campaign
- 3. MX Component Emissions
- 4. Government Agency Mandated
- 5. Retrofit
- 6. Prognostic
- 7. Fix-as-Fail
- 8. Information Only
- 9. Live Fault Code
- 10. Extended Service Agreement

A Live Fault Code becomes an open job only when the ATA component it names maps to a warrantable component. Every other authority is emitted directly from the SIR / SmartLINQ Service Management surface.

Sample fixture — what each VIN demonstrates

VIN suffix	Chassis	Demonstrates
...0101	579 MX, line haul	Campaign + prognostic stacking, inbound-tonight
...0202	579 MX, regional haul	Federal Safety Recall alone, inbound-this-week
...0303	567 severe service (logger)	MX VGT job routes to review lane on missing Prior Approval
...0404	579 MX, line haul, aged	Ineffective-repeat flag routes to review lane , out-of-region
...0505	537 Class 6/7	Class 6/7 recall path, inbound-tonight
...0606	220EV battery electric	BEV ESS campaign, bev_ess bucket

VIN suffix	Chassis	Demonstrates
...0707	579 MX, regional	Info-only bulletin scores 3.0 — no false urgency manufactured

Validating a row

```
cd warranty-gene
python3 scripts/validate.py
```

Expected output: one line per row, all OK , all valid.

Rebuilding the samples

```
cd warranty-gene
python3 scripts/build_samples.py
```

Deterministic. The same VIN + as_of date always produces the same row id.

Landing

- Public: warranty-gene/schema/ under the Hawkins Twin Platform.
- Private: rich-target worklists remain in Hawkins-owned Azure Postgres.

© 2026 EVEglyphDesign. All rights reserved. Controlled copy.

Key ID EgD-KEY-2026-07 .

Pour le bien-être du peuple.