

String(স্ট্রিং)

1(1) - Print using string.(স্ট্রিং এর মাধ্যমে প্রিন্ট করা)

1(2) – Print string from the user.

2(1) - Display string character wise

2(2) - Display string character wise

3(1) - Find a string length using strlen() function.

3(2) - Find a string length without using strlen() function.

4(1) - Copy a string using strcpy() function.

4(2) - Copy a string using strcpy() function from the user.

5(1) - Concat string using strcat() function.

5(2) - Concat string using strcat() function.

5(3) - Concat string without strcat() function.

6. Comparing a string using strcmp() function.

7(1).Reverse a string using strrev() function.

7(2).Reverse a string using strrev() function form the user.

7(3).Reverse a string without strrev() function.

8. String swapping(এক স্ট্রিং এর উপাদান অন্য স্ট্রিং এ কপি করা)

9. Checking a string palindrome or not.

10(1) –strupr()

10(2) –strlwr()

11(1).Determine number of vowels, cosonant, word, digitand others.

11(2).Determine number of capital and small letter

12.আউটপুট হিসাবে স্ট্রিং এর প্রতিটি শব্দ আলাদা লাইন এ প্রিন্ট হবে। বিরামচিহ্ন গুলো প্রিন্ট হবে না এবং শব্দের প্রথম অক্ষর হবে বড় হাতের।

13(1).Binary to Decimal.

13(2).Binary to Decimal from the user.

14(1).Decimal to Binary.

14(2).Decimal to Binary from the user.

1(1) - Print using string.(স্ট্রিং এর মাধ্যমে প্রিন্ট করা)

```
#include <stdio.h>

int main()
{
    char ch[] = "Golam Kibria";
    /*char ch[] = "Golam \
        kibria"; */
    printf("%s\n", ch);
}
```

Output:
Golam Kibria

1(2) - Print string from the user.

```
#include <stdio.h>

int main()
{
    char ch[20];
    printf("Enter your full name ");
    gets(ch);

    printf("Full name is = %s\n", ch);
}
```

Output:
Enter your full name Golam kibria
Full name is = Golam kibria

2(1) - Display string character wise

```
#include <stdio.h>

int main()
{
    char ch[] = "kibria";
    int i = 0;

    while (ch[i] != '\0')
    {
        printf("%c\n", ch[i]);
        i++;
    }
}
```

Output:
k
i
b
r
i
a

2(2) - Display string character wise

```
#include <stdio.h>

int main()
{
    char ch[] = "kibria";
    int length, i;
    length = strlen(ch);
    for (i = 0; i < length; i++)
    {
        printf("%c\n", ch[i]);
    }
}
```

Output:

k
i
b
r
i
a

3(1)- Find a string length using strlen() function.

```
#include <stdio.h>

int main()
{
    char ch[10] = "kibria";
    //scanf("%s", &ch);
    //printf("The string is = %s\n", ch);
    int length = strlen(ch);

    printf("Length is = %d\n", length);
}
```

Output:

Length is = 6

3(2)- Find a string length without using strlen() function.

```
#include <stdio.h>

int main()
{
    char ch[] = "kibria";
    int i = 0, length = 0;

    while (ch[i] != '\0')
    {
        i++;
        length++;
    }
    printf("Length is = %d\n", length);
    (০ তম ইনডেক্স মানে হলো ১ তম লেখ্য)
}
```

Output:

Length is = 6

4(1)- Copy a string using strcpy() function.

```
#include <stdio.h>

int main()
{
    char ch1[20] = "kibria";
    char ch2[20];

    strcpy(ch2, ch1);

    printf("Main string is = %s\n", ch1);
    printf("Copy string is = %s\n", ch2);
}
```

Output:
Main string is = kibria
Copy string is = kibria

4(2)- Copy a string using strcpy() function from the user.

```
#include <stdio.h>

int main()
{
    char ch1[20];
    char ch2[20];
    printf("Main string is = ");
    //scanf("%s", &ch1);
    gets(ch1);

    strcpy(ch2, ch1);

    printf("Copy string is = %s\n", ch2);
}
```

Output:
Main string is = Golam kibria
Copy string is = Golam kibria

5(1) - Concat string using strcat() function.

```
#include <stdio.h>

int main()
{
    char ch1[20] = "My name is ";
    char ch2[20] = "Golam kibria";

    strcat(ch1, ch2);

    printf("Character is = %s\n", ch1);
}
```

Output:
Character is = My name is Golam kibria

5(2) - Concat string using strcat() function.

```
#include <stdio.h>

int main()
{
    char ch1[20] = "My name is ";

    strcat(ch1, "Golam kibria");

    printf("Character is = %s\n", ch1);
}
```

Output:
Character is = My name is Golam kibria

5(3)- Concat string without strcat() function.

```
#include <stdio.h>

int main()
{
    char ch1[50] = "Golam ";
    char ch2[] = "kibria";
    int i = 0, length = 0, j = 0;

    while (ch1[i] != '\0')
    {
        i++;
        length++;
    }
    while (ch2[j] != '\0')
    {
        ch1[length + j] = ch2[j];
        j++;
    }
    //ch1 এর ৫তম ইনডেক্সে বসবে ch2 এর ০তম ইনডেক্স এর মান
    printf("Character is = %s\n", ch1);
}
```

Output:
Character is = Golam kibria

6. Comparing a string using strcmp() function.

```
#include <stdio.h>

int main()
{
    char ch1[10];    // = "kibria";
    char ch2[10];    // = "kibria";
    scanf("%s %s", &ch1, &ch2);
    printf("ch1 = %s\nch2 = %s\n", ch1, ch2);

    int d = strcmp(ch1, ch2);

    if (d == 0)
        printf("String are equal\n");
    else
        printf("Strings are not equal\n");
}
```

Output:
kibria
kibria
ch1 = kibria
ch2 = kibria
String are equal

7(1). Reverse a string using strrev() function.

```
#include <stdio.h>

int main()
{
    char ch[] = "kibria";
    printf("Character is = %s\n", ch);
    strrev(ch);

    printf("Reverse is = %s\n", ch);
}
```

Output:
Character is = kibria
Reverse is = airbik

7(2). Reverse a string using strrev() function form the user.

```
#include <stdio.h>

int main()
{
    char ch[10];
    printf("Character is = ");
    gets(ch);

    strrev(ch);
    printf("Reverse is = %s\n", ch);
}
```

Output:
Character is = golam kibria
Reverse is = airbik malog

7(3). Reverse a string without strrev() function.

```
#include <stdio.h>

int main()
{
    char ch1[20] = "kibria";
    char ch2[20];
    int i = 0, length = 0, j;
    //i and length for ch1 , j for ch2
    while (ch1[i] != '\0')
    {
        i++;
        length++;
    }

    for (j = 0, i = length - 1; i >= 0; i--, j++)
    {
        ch2[j] = ch1[i];
    }
    ch2[j] = '\0';

    printf("Character is = %s\n", ch1);
    printf("Reverse is = %s\n", ch2);
}
```

Output:
Character is = kibria
Reverse is = airbik

8. String swapping(এক স্ট্রিং এর উপাদান অন্য স্ট্রিং এ কপি করা)

```
#include <stdio.h>

int main()
{
    char ch1[20] = "Bangladesh";
    char ch2[20] = "Canada";
    char temp[20];

    printf("Before swapping : \n");
    printf("ch1 = %s\n", ch1);
    printf("ch2 = %s\n", ch2);

    strcpy(temp, ch1);
    strcpy(ch1, ch2);
    strcpy(ch2, temp);

    printf("After swapping : \n");
    printf("ch1 = %s\n", ch1);
    printf("ch2 = %s\n", ch2);
}
```

Output:
Before swapping :
ch1 = Bangladesh
ch2 = Canada
After swapping :
ch1 = Canada
ch2 = Bangladesh

9. Checking a string palindrome or not.

```
#include <stdio.h>

int main()
{
    char ch1[20] = "kibria";
    char ch2[20];
    int i = 0, length = 0, j;
    //i and length for ch1 , j for ch2

    //printf("Enter a string = ");
    //scanf("%s", &ch1);
    while (ch1[i] != '\0')
    {
        i++;
        length++;
    }

    for (j = 0, i = length - 1; i >= 0; i--, j++)
    {
        ch2[j] = ch1[i];
    }
    ch2[j] = '\0';

    printf("Entered string is = %s\n", ch1);
    printf("Reverse string is = %s\n", ch2);

    int d = strcmp(ch1, ch2);
    //সমান হলে d=0 হবে। কারন মাইনাস করলে 0 ই হবে

    if (d == 0)
        printf("String is palindrome\n");
    else
        printf("String is not palindrome\n");
}
```

Output:
Entered string is = kibria
Reverse string is = airbik
String is not palindrome

10(1) - strupr()

```
#include <stdio.h>

int main()
{
    char ch[] = "kibria";
    strupr(ch);
    printf("Character is = %s\n", ch);
}
```

Output:
Character is = KIBRIA

```
#include <stdio.h>

int main()
{
    char ch[10];
    gets(ch);
    strupr(ch);
    printf("Character is = %s\n", ch);
}
```

Output:
kibria go
Character is = KIBRIA GO

10(2) - strlwr()

```
#include <stdio.h>

int main()
{
    char ch[] = "KIBRIA";
    strlwr(ch);
    printf("Character is = %s\n", ch);
}
```

Output:
Character is = kibria

11(1). Determine number of vowels, consonant, word, digit and others.

```
#include <stdio.h>

int main()
{
    char str[100];
    int i, vowel, consonant, digit, word, other;
    i = vowel = consonant = digit = word = other = 0;

    printf("Enter a string = ");
    gets(str);

    while ((str[i]) != '\0')
    {
        if (str[i] == 'a' || str[i] == 'e' || str[i] == 'i' || str[i] ==
'o' || str[i] == 'u' ||
            str[i] == 'A' || str[i] == 'E' || str[i] == 'I' || str[i]
== 'O' || str[i] == 'U')
            vowel++;
        else if ((str[i] >= 'a' && str[i] <= 'z') || (str[i] >= 'A' &&
str[i] <= 'Z'))
            consonant++;
        else if (str[i] >= '0' && str[i] <= '9')
            digit++;
        else if (ch == ' ')
            word++;
        else
            other++;
        i++;
    }
    word++;
    /*space এর আগে 1 টা word অবশ্যই থাকবে,
    তাই সেই word টাকে এখানে increment করে দিলাম।*/
    printf("Number of vowels = %d\n", vowel);
    printf("Number of consonants = %d\n", consonant);
    printf("Number of words = %d\n", word);
    printf("Number of digits = %d\n", digit);
    printf("Number of others = %d\n", other);
}
```

Output:
Enter a string = Golam, Kibria, 34#ezaz
Number of vowels = 7
Number of consonants = 8
Number of words = 3
Number of digits = 2
Number of others = 3

11(2). Determine number of capital and small letter.

```
#include <stdio.h>

int main()
{
    char str[50];
    int i, capital, small, digit;
    i = capital = small = digit = 0;

    printf("Enter a string = ");
    gets(str);

    while (str[i] != '\0')
    {
        if (str[i] >= 65 && str[i] <= 90)
            capital++;
        else if (str[i] >= 97 && str[i] <= 122)
            small++;
        else if (str[i] >= 48 && str[i] <= 57)
            digit++;
        i++;
    }

    printf("Number of capital letter = %d\n", capital);
    printf("Number of small letter = %d\n", small);
    printf("Number of digits letter = %d\n", digit);
}
```

Output:
Enter a string = Golam Kibria 34
Number of capital letter = 3
Number of small letter = 8
Number of digits letter = 2

12. আউটপুট হিসাবে স্ট্রিং এর প্রতিটি শব্দ আলাদা লাইন এ প্রিন্ট হবে। বিরামচিহ্ন গুলো প্রিন্ট হবে না এবং শব্দের প্রথম অক্ষর হবে বড় হাতের।

```
#include <stdio.h>
#include <string.h>

int main()
{
    char s[100], ch;
    int i, length, wordstarted = 0;

    gets(s);
    length = strlen(s);

    for (i = 0; i < length; i++)
    {
        if (s[i] >= 'a' && s[i] <= 'z')
        {
            if (wordstarted == 0)
            {
                wordstarted = 1;
                ch = 'A' + s[i] - 'a';
                printf("%c", ch);
            }
            else
            {
                printf("%c", s[i]);
            }
        }
        else if ((s[i] >= 'A' && s[i] <= 'Z') || (s[i] >= '0' && s[i] <= '9'))
        {
            if (wordstarted == 0)
            {
                wordstarted = 1;
            }
            printf("%c", s[i]);
        }
        else
        {
            if (wordstarted == 1)
            {
                wordstarted = 0;
                printf("\n");
            }
        }
    }

    return 0;
}
```

Output:
golam kibria ezaz
Golam
Kibria
Ezaz

13(1). Binary to Decimal.

```
#include <stdio.h>
#include <math.h>
#include <string.h>
```

Output:
Decimal value is = 22

```
int main()
{
    char binary[] = "10110";
    int length = 5;
    int position = 4;
    int decimal = 0;
    int i;

    for (i = 0; i < length; i++)
    {
        decimal = decimal + (binary[i] - '0') * pow(2, position);
        position--;
    }
    printf("Decimal value is = %d\n", decimal);
}
```

13(2). Binary to Decimal from the user.

```
#include <stdio.h>
#include <math.h>
#include <string.h>
```

Output:
Enter the binary number = 111
Decimal value is = 7

```
int main()
{
    char binary[65];
    int length;
    int position;
    int decimal = 0;
    int i;

    printf("Enter the binary number = ");
    scanf("%s", &binary);

    length = strlen(binary);
    position = length - 1;

    for (i = 0; i < length; i++)
    {
        decimal = decimal + (binary[i] - '0') * pow(2, position);
        position--;
    }
    printf("Decimal value is = %d\n", decimal);
}
```

14(1). Decimal to Binary.

```
#include <stdio.h>

int main()
{
    int decimalnumber = 22;
    int binarynumber = 0;
    int rem, temp = 1;

    while (decimalnumber != 0)
    {
        rem = decimalnumber % 2;
        decimalnumber = decimalnumber / 2;
        binarynumber = binarynumber + rem * temp;
        temp = temp * 10;
    }

    printf("The binary number is = %d\n", binarynumber);
}
```

Output:
The binary number is = 10110

14(2). Decimal to Binary from the user.

```
#include <stdio.h>

int main()
{
    int decimalnumber;
    int binarynumber = 0;
    int rem, temp = 1;

    printf("Enter any decimal number = ");
    scanf("%d", &decimalnumber);

    while (decimalnumber != 0)
    {
        rem = decimalnumber % 2;
        decimalnumber = decimalnumber / 2;
        binarynumber = binarynumber + rem * temp;
        temp = temp * 10;
    }

    printf("The binary number is = %d\n", binarynumber);
}
```

Output:
Enter any decimal number = 12
The binary number is = 1100