



Quality With Care

Complete Range of Adhesives For Mattress & Upholstered Furniture



**Solvent Based
Water Based
Non - Flammable
Brushable
Sprayable**



Kenda Farben India Pvt. Ltd.

C - 21, Phase - II, Noida - 201305 (UP), India

Tel. No. : +91 - 120 - 4282118, 4282119, email : info@kendafarben.in

Product	Applications	Features	Pack Sizes
Thermoplastic Rubber Adhesive : Sprayable			
SAR 503	Chairs, sofas & mattresses. (PU foam to PU foam, fabric, metal, wood, rexine & synthetic leather)	One way, easy to apply, low odour, good heat resistance, high tack & high yield, short open time, excellent bond strength.	5 Ltrs., 25 Ltrs.
SAR 533	Automotive seats, chairs, sofas & mattresses. (PU foam to PU foam, EP foam, fabric, metal, wood, rexine & synthetic leather.)	Two ways, easy to apply, multi - purpose, low odour, good heat resistance, high coverage & high bonding strength.	5 Ltrs., 25 Ltrs.
SAR 534	Chairs, sofas & mattresses. (PU foam to PU foam, EP foam, fabric, metal, wood, leather & rexine.)	Two ways, easy to apply, low odour, short open time, high bond strength, good heat resistance & superior coverage.	5 Ltrs., 25 Ltrs.
SAR 373	Automotive seats, chairs, sofas & mattresses. (PU foam to PU foam, EP foam, fabric, metal, wood, rexine & synthetic leather.)	Two ways, easy to apply, multi - purpose, low odour, good heat resistance, high coverage & high bonding strength.	5 Ltrs., 20 Ltrs., 25 Ltrs.
SAR 432	Automotive seats, chairs, sofas & mattresses. (PU foam to PU foam, EP foam, fabric, metal, wood, rexine & synthetic leather.)	Two ways, easy to apply, multi - purpose, low odour, good heat resistance, high coverage & high bonding strength.	5 Ltrs., 20 Ltrs., 25 Ltrs.
Thermoplastic Rubber Adhesive : Sprayable (Non - Flammable)			
SAR 941	All types of mattresses. (Bonded foam, coir, EP foam, memory foam & spring mattresses)	Two ways, easy to apply, excellent bond strength, short open time & good heat resistance.	5 Ltrs., 25 Ltrs.
SAR 388	All types of mattresses. (Bonded foam, coir, EP foam, memory foam & spring mattresses)	Two ways, easy to apply, excellent bond strength, short open time & good heat resistance.	5 Ltrs., 25 Ltrs.
SAR 429	All types of mattresses. (Bonded foam, coir, EP foam, memory foam & spring mattresses)	Two ways, easy to apply, excellent bond strength, short open time & good heat resistance.	5 Ltrs., 25 Ltrs.
Synthetic Rubber Adhesives : Sprayable			
SAR 523	Suitable for bonding of fabric & rubber foam to fabric, foam rexine, metal, wood etc.	Easy to apply, good heat resistance, high tack & high coverage, long open time & high bond strength.	5 Ltrs., 25 Ltrs.
SAR L200	Suitable for bonding of fabric & rubber foam to fabric, foam rexine, metal, wood etc.	Easy to apply, good heat resistance, high tack & high coverage, long open time & high bond strength.	5 Ltrs., 25 Ltrs.
Synthetic Rubber Adhesive : Brushable			
SAR 70E	For bonding leather, rubber & non - woven fabric, EP foam, PU foam, vinyl sheet, rexine etc.	Easy to apply, high tack & high bonding strength, long open time & good heat resistance.	5 Ltrs., 25 Ltrs.
SAR 73 ECO	For bonding leather, rubber & non - woven fabric, EP foam, PU foam, vinyl sheet, rexine etc.	Easy to apply, good tack & high bonding strength, long open time & good heat resistance.	5 Ltrs., 25 Ltrs.
SAR 74 ECO	For bonding leather, rubber & non - woven fabric, EP foam, PU foam, vinyl sheet, rexine etc.	Easy to apply, good tack & high viscosity, good bonding strength, long open time & good heat resistance.	5 Ltrs., 25 Ltrs.
SAR 215	For bonding leather, rubber fabric, EVA, foam, vinyl sheet, rexine, synthetic leather etc.	Easy to apply, long open time, high tack & excellent bond strength, & very good heat resistance.	5 Ltrs., 25 Ltrs.
SAR 160	For bonding leather, rubber fabric, EVA, foam, vinyl sheet, rexine, synthetic leather etc.	Easy to apply, high heat resistance, long open time, high tack & outstanding bond strength.	5 Ltrs., 25 Ltrs.
Bi - Component Water Based Spray Adhesive			
ECOSAR 502B	Chairs, sofas & mattresses. (Foam to foam, fabric, metal wood, rexine & synthetic leather.)	Eco - friendly, easy to apply, low odor & low VOC, high heat resistance, instant bonding, medium open time, excellent bond strength.	5 Kgs., 20 Kgs.
Catalyst For Water Based Adhesives			
KENDOR ECO A	It has to be used combined with the adhesive ECOSAR 502B, before spraying, according to the desired setting time.	Catalyst in watery dispersion, used in combination with ECOSAR 502B.	5 Kgs., 20 Kgs.
Application Process : It is applied by special spraying system combined with the catalyst KENDOR ECO A, suggested quantity : 10 - 15% by special bi - component spray machine. The spraying distance to be adjusted for homogenous spraying onto the surface to be bonded and then, join the two substrates immediately after the application.			