

The 'sopra-changelog' Package

Documentation for the 'sopra-changelog' package | Version v1.0.02

2. December 2019

Florian Sihler (florian.sihler@uni-ulm.de)

1 General

1.1 Why, what for?

This $\text{\LaTeX}$ package was written as part of the Sopra in the winter semester 2019 and summer semester 2020 and serves for the automatic generation of changelogs for *Team 20*. This documentation was created together with the `sopra-base.cls` as well as the `sopra-documentation.sty` package.

The `sopra-listings` package is used to visualize the individual code excerpts. The associated package should also be embedded in this document: . This package was developed and programmed within three hours; it is currently under development.

1.2 Dependencies

This package includes the following packages:

- `environ`
- `fontawesome`
- `marginfix`
- `hyperref`

All of these packages should be part of a common $\text{\LaTeX}$ distribution.

1.3 Installation

The package is not delivered as a `.dtx`, which is why the following options arise:

- The package can be placed in the same directory as the document. In this case the inclusion instruction reads:

```
\usepackage{sopra-changelog}
```

- The package can be placed in a subdirectory/a directory shipped with the document. In this case it is specified via the (relative) path:

```
\usepackage{./My/Path/to/sopra-changelog}
```

- The package can be placed (via a symlink or similar) in one's own `texmf` tree. For example, on Linux using `texlive`, the package can be placed here: `~/texmf/tex/latex/`. The directory can be created and then updated using `texhash ~/texmf`. Now the package can be used like any other installed package:

```
\usepackage{sopra-changelog}
```

1.4 Further peculiarities

In version v1.0.02 (`\thesocversion`^{→ p. 3}) there are no further peculiarities.

2 Package Configuration

2.1 Accepted Parameters

In version v1.0.02 no parameters are accepted.

3 Commands and Environments

Note that the prefix `env@` only indicates the nature of an environment and is not part of the actual identifier!

Also: For the changes to be resolved correctly, the document usually has to be compiled twice to produce a correct display.

3.1 Specifying Version Changes

▷ `env@version[changes]{Introduced Version}{Title}`

The main environment of the package, used for versioning. An important note upfront: *The content of the environment is only typeset if `\setTargetVersion`^{P. 3} is set to at least Introduced Version! Otherwise the change doesn't exist yet.*

The field Introduced Version specifies the version number (counted from 1) with which the components enclosed in the environment become available. These are identified by the *unique* title in Title.

The most important field, however, is changes. Here a comma-separated list of fields can be passed, which must follow either the syntax “changed in: <VerID> (<Description>)” or the syntax “removed in: <VerID> ↔ (<Description>)”. An example:

```
1 \begin{version}[%
2   changed in: 2 (Added Some funny stuff),%
3   changed in: 3 (Removed stupid sentences),%
4   removed in: 4 (Rendered to be stupid!)
5 ]{1}{Coordinates of the Game Board}
6   Now anything one can imagine can go here. Also normal \LaTeX\ code!
7 \end{version}
```

This produces (note: this document was compiled with `\setTargetVersion{5}`):
Now anything one can imagine can go here. Also normal $\LaTeX$ code!

● V. 1-4

▷ `\simpleversion[changes]{Introduced Version}{Title}{Content}`

Simply a small wrapper that calls `env@version`^{P. 2} with Content.

▷ `\setVersionData{Version ID}{Version Date}{Version Description}`

Stores metadata for `\thechangelog`^{P. 2} regarding the version with version number Version ID. The Version-Date must be given in YYYY-MM-DD format!

3.2 Typesetting Version Changes

▷ `\thechangelog`

Typesets the history of all changes. `\section` and `\subsection` are used for the structure. An example can be found at the end of the document.

3.3 Assigning Further Data

▷ `\setTargetVersion{VersionID}`

Ensures that all changes up to version `VersionID` are output (with regard to the changelog). This value should be incremented with each change cycle. *So far no automated solution is planned!*

▷ `\setTargetVersionDate{Date}`

Has no meaning so far!

3.4 Helpful Commands

▷ `\thesocversion`

Outputs the current version of the sopra-paper document class. Note: via `\value{socversion}` the version can be obtained as a 4-digit number: 1002.

4 Changelog

4.1 Changelog for version 1

❗ No information is available for this version.

⊕ *Coordinates of the Game Board*: New element!

4.2 Changelog for version 2

❗ No information is available for this version.

- *Coordinates of the Game Board*: Added Some funny stuff

4.3 Changelog for version 3

❗ No information is available for this version.

- *Coordinates of the Game Board*: Removed stupid sentences

4.4 Changelog for version 4 (2. December 2019)

❗ Everything was totally super here. This version adds monkeys!

⊗ *Coordinates of the Game Board*: Rendered to be stupid!