

The 'sopra-documentation' package

Documentation for the 'sopra-documentation' package | Version v1.1.02

2. December 2019

Florian Sihler (florian.sihler@uni-ulm.de)

1 General

1.1 Why, wherefore, what for?

This $\text{\LaTeX}$ package was written as part of the Sopra in the 2019 winter semester and 2020 summer semester and serves as the foundation for creating documentation for the other packages and classes of *Team 20*, which are created together with `sopra-base.cls`.

To visualize the individual code excerpts, the `sopra-listings` package is used. It is not relevant for the use of the package (`nolistings`).

The associated package should also be embedded in this document: .

1.2 Dependencies

This package includes the following packages:

- `xcolor`
- `multicol`
- `blindtext` (only dummy)
- `attachfile2`
- `sopra-listings` (only listings)
- `hyperref`

All of these packages should be part of the common $\text{\LaTeX}$ distribution or shipped alongside it.

1.3 Installation

The package is not shipped as a `.dtx`, which is why the following options are available:

- The package can be placed in the same directory as the document. In this case, the inclusion instruction is:
`\usepackage{sopra-documentation}`
- The package can be placed in a subdirectory/in a directory shipped with the document. In this case, it is specified via the (relative) path:
`\usepackage{./My/Path/to/sopra-documentation}`
- One can place the package (via a symlink or similar) into one's own `texmf` tree. For example, on Linux using `texlive`, the package can be placed here: `~/texmf/tex/latex/`. The directory can be created and subsequently updated via `texhash ~/texmf`. Now the package can be used like any other installed package:
`\usepackage{sopra-documentation}`

1.4 Further peculiarities

v1.0.0:

In this version there are no further peculiarities.

v1.1.02:

In this version LILLYxLISTINGS was replaced by sopra-listings!

2 Package configuration

2.1 Accepted parameters

Like most, the package accepts arguments. For arguments with a “counter” option, the one active by default is written first and the other in brackets. So implicitly:

```
\usepackage[nodebug,dummy,listings]{sopra-documentation}
```

is invoked. Whereas with:

```
\usepackage[nolistings]{sopra-documentation}
```

we compile the document without the LILLYxLISTINGS package.

- ▷ nodebug (debug)

In debug mode, the log is made more verbose thanks to `\errorcontextlines` (in case of an error).

- ▷ dummy (nodummy)

In dummy mode, the `blindtext` package is included, otherwise not.

- ▷ listings (nolistings)

In listings mode, the LILLYxLISTINGS package is included, otherwise not.

3 Commands and environments

Note that the prefix `env@` only indicates the nature of an environment and is not to be considered part of the actual identifier!

3.1 Compatibility mode

This mode is not available in v1.1.02!

These commands are only defined with `nolistings`, since otherwise they would be included by LILLYxLISTINGS:

- ▷ `\T{Text}`

Implemented here as an alias for `\texttt`; sets `Text` in typewriter font.

- ▷ `\lstcomment{Text}`

Similarly, `\lstkwone`, `\lstkwtwo`, `\lstkwthree`, `\lstkwfour`, `\lstkwfive`, `\lstkwsix`, `\lststring` and `\lstnumber` exist, which highlight `Text` in color.

3.2 General commands

▷ `\email{E-Mail}`

Sets E-Mail as a clickable e-mail address.

▷ `\thesodversion`

Returns the current version of the package. So `\thesodversion` yields: v1.1.02

Note: via `\value{sodversion}` the version can be obtained as a 4-digit number: 1102.

▷ `\manArg{Text}`

Allows a mandatory argument to be specified in `env@command→P. 3` or comparable environments. For example, Text in the command definition is set using `\manArg!`

▷ `\optArg{Text}`

Allows an optional argument to be specified in `env@command→P. 3` or comparable environments.

▷ `\cmd{Name}`

Sets Name as a command: `\cmd{Hi}`: `\Hi`.

▷ `\env{Name}`

Sets Name as an environment: `\env{Hi}`: `env@Hi`.

▷ `\cmdref{Name}`

Similar to `\cmd→P. 3`, however (just as here) a link to the explanation of Name is created.

▷ `\envref{Name}`

Similar to `\env→P. 3`, however a link to the explanation of Name is created.

▷ `\argref{Name}{Counter}`

Sets an argument with the corresponding counter option.

▷ `env@command{Name}{Arguments}`

Starts the explanation of a new command with identifier Name (for `\cmdref→P. 3`) and the arguments Arguments.

▷ `env@environment{Name}{Arguments}`

Starts the explanation of a new environment with identifier Name (for `\envref→P. 3`) and the arguments Arguments (as here).

- ▷ `env@argument{Name}{Counter-Name}`

Starts the explanation of a new argument for the package/class with identifier `Name` and the counter identifier `Counter-Name`.

- ▷ `\say{Text}`

Sets `Text` in “quotation marks”.

- ▷ `\jmark[Text]{LinkTarget}`

Works analogously to its counterpart in Lilly, because I like it better that way and write it out of reflex :D.

3.3 Further commands

These commands originate from the included packages and are merely configured here.

- ▷ `\attachfile[Options]{Path}`

Embeds the file at `Path`. As `Options`, at least `subject` is worth using. For example, in this documentation the package is embedded with the following line:

```
\attachfile[subject={sopra-documentation.sty}]{sopra-documentation.sty}
```

- ▷ `\textattachfile[Options]{Path}{Text}`

Embeds the file at `Path`, but instead of a symbol makes `Text` the clickable link to open it. The options are analogous to `\attachfile` → p. 4.

For all other methods used, it is recommended to take a closer look at the source code itself or the source code of the documentation.