www.tntextbooks.in

(3)Logical Operators

A logical operator is used to evaluate logical and relational expressions. The logical operators act upon the operands that are themselves called as logical expressions. C++ provides three logical operators.

Table 9.3 Logical Operators

Operator	Operation	Description
&&	AND	The logical AND combines two different relational expressions in to one. It returns 1 (True), if both expression are true, otherwise it returns 0 (false).
||	OR	The logical OR combines two different relational expressions in to one. It returns 1 (True), if either one of the expression is true. It returns 0 (false), if both the expressions are false.
!	NOT	NOT works on a single expression / operand. It simply negates or inverts the truth value. i.e., if an operand / expression is 1 (true) then this operator returns 0 (false) and vice versa

- AND, OR both are binary operators where as NOT is an unary operator.

Example: a = 5, b = 6, c = 7;

Expression	Result
(a<b) && (b<c)	1 (True)
(a>b) && (b<c)	0 (False)
(a<b) || (b>c)	1 (True)
!(a>b)	1 (True)

(4)Bitwise Operators

Bitwise operators work on each bit of data and perform bit-by-bit operation. In C++, there are three kinds of bitwise operators, which are:

(i) Logical bitwise operators

(ii) Bitwise shift operators

(iii) One's compliment operators