In C++, one or two operators may be used in different places with different meaning. For example: Asterisk (*) is used for multiplication as well as for pointer to a variable.

9.3.5 Punctuators

Punctuators are symbols, which are used as delimiters, while constructing a C++ program. They are also called as **"Separators".** The following punctuators are used in C++; most of these symbols are very similar to C and Java.

Separator	Description	Example

Curly braces { }	Opening and closing curly braces indicate the start and the end of a block of code. A block of code containing more than one executable statement. These statements together are called as "compound statement"	int main ( )
		{
		int x=10, y=20, sum;
		sum = x + y;
		cout << sum;
		}

Parenthesis ( )	Opening and closing parenthesis indicate function calls and function parameters.	clrscr( ); int main ( )
Square brackets [ ]	It indicates single and multidimensional arrays.	int num[5]; char name[50];
Comma ,	It is used as a separator in an expression	int x=10, y=20, sum;

Semicolon ;	Every executable statement in C++ should terminate with a semicolon	int main ( )
		{
		int x=10, y=20, sum;
		sum = x + y;
		cout << sum;
		}

Colon :	It is used to label a statement.	private:

Comments
//
/* */
	Any statement that begins with // are considered as comments. Comments are simply ignored by compilers. i.e., compiler does not execute any statement that begins with a //
	// Single line comment
	/* …….. */ Multiline comment
		/* This is written
		By myself
		to learn CPP */
		int main ( )
		{
		int x=10, y=20, sum;
		// to sum x and y
		sum = x + y;
		cout << sum;
		}