www.tntextbooks.in

Another program illustrates how **int** and **char** data types are working together.

**Illustration 9.3: C++ program to get an ASCII value and display the corresponding character**

```
#include <iostream>
using namespace std;
int main ()
{
        int n;
        char ch;
        cout << "\n Enter an ASCII code (0 to 255): ";
        cin >> n;
        ch = n;
        cout << "\n Equivalent Character: " << ch;
}
```

**The output**

```
Enter an ASCII code (0 to 255): 100
Equivalent Character: d
```

In the above program, variable **n** is declared as an int type and another variable **ch** as a char type. During execution, the program prompts the user to enter an ASCII value. If the user enters an ASCII value as an integer, it will be stored in the variable **n**. In the statement **ch = n**; the value of **n** is assigned into **ch**. Remember that, **ch** is a char type variable.

For example, if a user enters 100 as input; initially, 100 is stored in the variable **n**. In the next statement, the value of **n** i.e., 100 is assigned to **ch**. Since, **ch** is a char type; it shows the corresponding ASCII character as output. (Equivalent ASCII Character for 100 is d).

### (3) float data type:

If a variable is declared as float, all values will be stored as floating point values.

**There are two advantages of using float data types.**

(1) They can represent values between the integers.

(2) They can represent a much greater range of values.

At the same time, floating point operations takes more time to execute compared to the integer type ie., floating point operations are slower than integer operations. This is a disadvantage of floating point operation.