In the above program, some unknown values will be occupied in memory that is allocated for the variables **num1** and **num2;** and the statement c**out << num1 + num2;** will display the sum of those unknown junk values.

9.13.2 Initialization of variables:

Assigning an initial value to a variable during its declaration is called as "Initialization".

Examples:

int num = 100;

float pi = 3.14;

double price = 231.45;

Here, the variables num, pi, and price have been initialized during the declaration. These initial values can be later changed during the program execution.

Illustration 9.6 C++ Program to find the Curved Surface Area of a cylinder (CSA) (CSA = 2 pi r * h)

```
#include <iostream>
using namespace std;
int main()
{
        float pi = 3.14, radius, height, CSA;
        cout << "\n Curved Surface Area of a cylinder";
        cout << "\n Enter Radius (in cm): ";
        cin >> radius;
        cout << "\n Enter Height (in cm): ";
        cin >> height;
        CSA = (2*pi*radius)*height;
        system("cls");
        cout << "\n Radius: " << radius <<"cm";
        cout << "\n Height: " << height << "cm";
        cout << "\n Curved Surface Area of a Cylinder is " << CSA <<" sq. cm.";
}
```

Output:

```
 Curved Surface Area of a cylinder
 Enter Radius (in cm): 7
 Enter Height (in cm): 20
 Radius: 7cm
Height: 20cm
Curved Surface Area of a Cylinder is 879.2 sq. cm.
```