www.tntextbooks.in

cout << "The value of num = " << num <<**end;**

Both these statements display the same output.

setw ( )

setw manipulator sets the **width of the field** assigned for the output. The field width determines the minimum number of characters to be written in output.

Syntax:

setw(number of characters)

Example:

Illustration 9.10: Program to Calculate Net Salary

```
#include <iostream>
#include <iomanip>
using namespace std;
int main()
{
        float basic, da, hra, gpf, tax, gross, np;
        char name[30];
        cout << "\n Enter Basic Pay: ";
        cin >> basic;
        cout << "\n Enter D.A : ";
        cin >> da;
        cout << "\n Enter H.R.A: ";
        cin >> hra;
        gross = basic+da+hra; // sum of basic, da nad hra
        gpf = (basic+da) * 0.10; // 10% 0f basic and da
        tax = gross * 0.10; //10% of gross pay
        np = gross - (gpf+tax); //netpay = earnings - deductions
        cout << setw(25) << "Basic Pay : " << setw(10)<< basic<< endl;
        cout << setw(25) << "Dearness Allowance : "<< setw(10)<<da<< endl;
        cout<<setw(25)<<"House Rent Allowance : "<<setw(10)<< hra<<endl;
        cout << setw(25) << "Gross Pay : " << setw(10) << gross << endl;
        cout << setw(25) << "G.P.F : " << setw(10) << gpf << endl;
        cout << setw(25) << "Income Tax : " << setw(10)<< tax << endl;
        cout << setw(25) << "Net Pay : " << setw(10) << np << endl;
}
```