www.tntextbooks.in

following the call statement. This reduces the speed of program execution. Inline functions can be used to reduce the overheads like STACKS for small function definition.

An inline function looks like normal function in the source file but inserts the function's code directly into the calling program. To make a function inline, one has to insert the keyword **inline** in the function header.

Syntax :

inline returntype functionname(datatype parametername1, … datatype parameternameN)

Advantages of inline functions:

- Inline functions execute faster but requires more memory space.
- Reduce the complexity of using STACKS.

Program 11.19

```
#include <iostream>
using namespace std;
inline float simpleinterest(float p1,float n1, float r1)
{
        float si1=(p1*n1*r1)/100;
        return(si1);
}
int main ()
{
        float  si,p,n,r;
        cout<<"\nEnter the Principle Amount Rs. :";
        cin>>p;
        cout<<"\nEnter the Number of Years     :";
        cin>>n;
        cout<<"\nEnter the Rate of Interest    :";
        cin>>r;
        si=simpleinterest(p,n,r);
        cout << "\nThe Simple Interest = Rs."<<si;
        return 0;
}
```

Output:

```
Enter the Principle Amount Rs. :60000
Enter the Number of Years     :10
Enter the Rate of Interest    :5
The Simple Interest = Rs.30000
```