www.tntextbooks.in

Write a program to demonstrate various methods of initializing the character arrays

```
#include <iostream>
using namespace std;

int main()
{
        char arr1[6]="INDIA";
        char arr2[6]={'I','N','D','I','A','\0'};
        char arr3[]="TRICHY";
        char arr4[]={'T','R','I','C','H','Y','\0'};
        char arr5[8]="TRICHY";
        cout<<"arr1  is :" <<arr1<< " and its size is "<<sizeof(arr1)<<endl;
        cout<<"arr2  is :" <<arr2<< " and its size is "<<sizeof(arr2)<<endl;
        cout<<"arr3  is :" <<arr3<< " and its size is "<<sizeof(arr3)<<endl;
        cout<<"arr4  is :" <<arr4<< " and its size is "<<sizeof(arr4)<<endl;
        cout<<"The elements of arr5"<<endl;
        for(int i=0;i<8;i++)
        cout<<arr5[i]<<" ";
        return 0;
}
```

Output

```
arr1  is :INDIA and its size is 6
arr2  is :INDIA and its size is 6
arr3  is :TRICHY and its size is 7
arr4  is :TRICHY and its size is 7
The elements of arr5
T R I C H Y
```

Read a line of Text

In C++, cin.get() is used to read a line of text including blank spaces. This function takes two arguments. The first argument is the name of the string and second argument is the maximum size of the array.