www.tntextbooks.in

```
{
ShoeType shoe1, shoe2;
shoe1.name = "Adidas";
shoe1.price = 9.99;
cout<< shoe1.name<< " # "<< shoe1.price<<endl;
shoe2 = shoe1;
shoe2.price = shoe2.price / 9;
cout<< shoe2.name<< " # "<< shoe2.price;
return 0;
```

| | | | |
|---|---|---|---|
| (a) Adidas # 9.99<br>Adidas # 1.11 | (b) Adidas # 9.99<br>Adidas # 9.11 | (c) Adidas # 9.99<br>Adidas # 11.11 | (d) Adidas # 9.11<br>Adidas # 11.11 |

7. Which of the following is a properly defined structure?

   (a) struct {int num;} (b) struct sum {int num;}

   (c) struct sum int sum; (d)struct sum {int num;};

8. A structure declaration is given below.

```
struct employee
{
int empno;
char ename[10];
}e[5];
```

   Using above declaration which of the following statement is correct.

   (a) cout<<e[0].empno<<e[0].ename; (b) cout<<e[0].empno<<ename;

   (c)cout<<e[0]->empno<<e[0]->ename; (d) cout<<e.empno<<e.ename;

9. Which of the following cannot be a structure member?

   (a) Another structure (b) Function

   (c) Array (d) variable of double datatype

10. When accessing a structure member ,the identifier to the left of the dot operator is the name of

    (a) structure variable (b) structure tag

    (c) structure member (d) structure function