www.tntextbooks.in

14.6 Functions in a class

A wide range of operations for the class members are performed using member functions of the class .These operations are defined in the member function.

14.6.1 Objects accessing inline and outline member functions

As you are aware the definition of the member function can be given either inside the class specification or outside the class

Let us see from the illustrated example program. This program defines a class called sales with the following description

private members of class salesman	
sno	integer(salesperson number)
sname	15 characters
hrwrk ,wage	float (hours worked and wage per hour)
totwage	float(*hrwrk * wage*)
calcwg( )	a function to find *hrwrk * wage* and store it in *totwage*
public members of class salesman	
in_data( )	a function to accept values for *sno*, *sname*, *hrwrk*, *wage* and invoke calcwg( ) to calculate *totwage*
out_data( )	a function to display all the data members on the screen. you should give definitions of functions as outline

Illustration 14.6 Inline Outline and function

```
#include<iostream>
using namespace std
class sales
{
        int sno;
        char sname [15];
        float hrwrk,wage,totwage;
void calcwg( )
        {
                totwage=hrwrk * wage;
        }
public :
        void in_data();
        void out_data();
};
```

An inline member function definition should be placed above all the functions that call it

The prototype of the outline member function given in a class specification, instructs the compiler about its visibility mode.