www.tntextbooks.in

MEMBERS of class	visibility modes –public for acquiring the properties of the base class		
	Private	Protected	Public
Shape(base class)	int count;	int width; int height;	void setWidth(int) void setHeight(int)
Rectangle (derived class acquired the properties of base class with public visibility)	Private members of base classes are not directly accessible by the derived class	int width; int height;	int getArea(); void setWidth(int) void setHeight(int)

Suppose the class **rectangle is derived with protected visibility** then the properties of class rectangle will change as follows

MEMBERS of class	visibility modes –protected for acquiring the properties of the base class		
	Private	Protected	Public
Shape(base class)	int count;	int width; int height;	void setWidth(int) void setHeight(int)
Rectangle (derived class acquired the properties of base class with protected visibility)	Private members of base classes are not directly accessible by the derived class	int width; int height; void setWidth(int) void setHeight(int)	intgetArea();

In case the class rectangle is derived with private visibility mode from its base class shape then the property of class rectangle will change as follows

MEMBERS of class	visibility modes –private for acquiring the properties of the base class		
	Private	Protected	Public
Shape(base class)	int count;	int width; int height;	void setWidth(int) void setHeight(int)
Rectangle (derived class acquired the properties of base class with private visibility)	Private members of base classes are not directly accessible by the derived class	int width; int height; void setWidth(int) void setHeight(int)	int getArea();