2. ஒரே மதிப்பு இரண்டு case கூற்றுகளில் அனுமதிக்கப்பட மாட்டாது.

3. default கூற்று கட்டாயமில்லை.

4. switch கூற்றின் நிரல் தொகுதியை நிறைவு செய்ய break கூற்று பயன்படுகிறது. நிரல் பாய்வு break கூற்றை அடையும் போது, switch கூற்றிலிருந்து வெளியேறி, switch கூற்றை தொடர்ந்து கொடுக்கப்பட்டுள்ள நிரல் கூற்றுகளை இயக்கும்.

5. break கூற்று கொடுப்பது கட்டாயமில்லை. break கூற்று கொடுக்கப்படவில்லை எனில், case நிபந்தனை நிறைவேற்றப்படும் நிரல் கூற்றை தொடர்ந்து உள்ள அனைத்து கூற்றுகளும் கட்டுப்பாடின்றி இயங்கும்.

6. பின்னலான switch கூற்றுகளும் அமைக்கப்படும்.

எடுத்துக்காட்டு 10.8 – switch கூற்றை விளக்கும் C++ நிரல்

```
#include <iostream>
using namespace std;
int main()
{
        int num;
        cout << "\n Enter week day number: ";
        cin >> num;
        switch (num)
        {
                case 1 : cout << "\n Sunday"; break;
                case 2 : cout << "\n Monday"; break;
                case 3 : cout << "\n Tuesday"; break;
                case 4 : cout << "\n Wednessday"; break;
                case 5 : cout << "\n Thursday"; break;
                case 6 : cout << "\n Friday"; break;
                case 7 : cout << "\n Saturday"; break;
                default: cout << "\n Wrong input....";
        }
}
```

வெளியீடு:

```
        Enter week day number: 6
        Friday
```


Chapter 10.indd 67 03/09/18 4:13 PM