குறியுரு அணிகளுக்கு தொடக்க மதிப்பிருத்துவதற்காக பல்வேறு முறைகளை விளக்கும் நிரல்

```
#include <iostream>
#include<conio.h>
using namespace std;

int main()
{
        char arr1[6]="INDIA";
        char arr2[6]={'I','N','D','I','A','\0'};
        char arr3[]="TRICHY";
        char arr4[]={'T','R','I','C','H','Y','\0'};
        char arr5[8]="TRICHY";
        cout<<"arr1  is :" <<arr1<< " and its size is "<<sizeof(arr1)<<endl;
        cout<<"arr2  is :" <<arr2<< " and its size is "<<sizeof(arr2)<<endl;
        cout<<"arr3  is :" <<arr3<< " and its size is "<<sizeof(arr3)<<endl;
        cout<<"arr4  is :" <<arr4<< " and its size is "<<sizeof(arr4)<<endl;
        cout<<"The elements of arr5"<<endl;
        for(int i=0;i<8;i++)
        cout<<arr5[i]<<" ";
        getch();
        return 0;
}
```

வெளியீடு:

```
        arr1  is :INDIA and its size is 6
        arr2  is :INDIA and its size is 6
        arr3  is :TRICHY and its size is 7
        arr4  is :TRICHY and its size is 7
        The elements of arr5
        TRICHY
```

ஒரு வரி உரையை படிக்க

C++ மொழியில் cin.get( ) என்ற செயற்கூறானது வெற்று இடைவெளிகளுடன் கூடிய ஒரு முழு நீள வரியை உள்ளீடாக பெற பயன்படுகிறது. இந்த செயற்கூறு இரண்டு செயலுருபுகளை ஏற்கும். முதல் செயலுருபு சரத்தின் பெயரையும் இரண்டாவது செயலுருபு அணியின் அதிகப்படியான அளவையும் குறிக்கும்.

get( )செயற்கூறுவை பயன்படுத்தி ஒரு வரி உரையை உள்ளிடுவதற்கான நிரல்

```
// str10.cpp
// To read a line of text
#include <iostream>
using namespace std;
int main()
{
charstr[100];
```


Chapter 12.indd 139 03/09/18 5:08 PM