```
voidreadData(Employee&);
voidprintData(Employee);
int main()
{
        Employee p;
        readData(p);
        printData(p);
return 0;
}
void readData(Employee &p) {
        cout<< "Enter Full name: ";
cin.get(p.name, 50);
        cout<< "Enter age: ";
        cin>>p.age;
        cout<< "Enter salary: ";
        cin>>p.salary;
}
voidprintData(Employee p)
{
        cout<< "\nDisplaying Information." <<endl;
        cout<< "Name: " << p.name <<endl;
        cout<<"Age: " <<p.age<<endl;
        cout<< "Salary: " <<p.salary;
}
```

வெளியீடு:

```
Enter Full name: Kumar
Enter age: 55
Enter salary: 34233.4
Displaying Information.
Name: Kumar
Age: 55
Salary: 34233.4
```

இந்த நிரலின் வெளியீடானது முந்தைய நிரலின் வெளியீட்டை போன்றே இருக்கும்.

2.குறிப்பு மூலம் அழைத்தல்

இந்த முறையில் ஒரு செயற்கூறினுக்கு அளபுருக்களை அனுப்பும் போது, கட்டுரு மாறி (அ) பொருளின் முகவரியானது செயற்கூறினுக்கு முகவரி செயற்குறியை (& address of operator) பயன்படுத்தி அனுப்பப்படுகிறது. எனவே, செயற்கூறினுள் உள்ள கட்டுரு மாறியின் உறுப்புகளில் எந்த வித மாற்றத்தை செய்தாலும், அது அழைப்புக் கூற்றினுள் பிரதிபலிக்கும்.

பின்வரும் எடுத்துக்காட்டானது குறிப்பு மூலம் swap() செயற்கூறினை அழைக்கிறது.

Chapter 12.indd 164 03/09/18 5:08 PM