```
cout<<"\n Comp.sci.. "<<mark5;
cout<<"\n Maths ..   "<<mark6;
}
 };
  class hexam : public student            //derived class with single base class
 {
    public:
           int  mark1, mark2 ,mark3,mark4,mark5,mark6;
   void acceptmark()
   {
     cout<<"\n Enter lang,eng,phy,che,csc,mat marks for halfyearly exam.. ";
     cin>>mark1>>mark2>>mark3>>mark4>>mark5>>mark6;
  }
void displaymark()
{
cout<<"\n\t\t Marks Obtained in Halfyearly";
cout<<"\n Language.. "<<mark1;
cout<<"\n English .. "<<mark2;
cout<<"\n Physics .. "<<mark3;
cout<<"\n Chemistry.. "<<mark4;
cout<<"\n Comp.sci.. "<<mark5;
cout<<"\n Maths ..   "<<mark6;
}
 };
int main()
{
  qexam q1;
  hexam h1;
 q1.acceptname();      //calling base class function using derived class object
 q1.acceptmark();       //calling base class function
 h1.acceptname();      //calling base class function using derived class object
 h1.displayname();    //calling base class function using derived class object
 h1.acceptmark();
 h1.displaymark();        //calling base class function using its
                           //derived class object
  return 0;
}
```


Chapter 16.indd 271 03/09/18 5:51 PM