$$d = \frac{1}{2} g t^2$$

Substituting $g = 9.8$ m s^{-2} we get the depth of the well.



To estimate the error in our calculation we can use another method to measure the depth of the well. Take a long rope and hang the rope inside the well till it touches the bottom. Measure the length of the rope which is the correct depth of the well ($d_{correct}$). Then

$$error = d_{correct} - d$$

$$relative\ error = \frac{d_{correct} - d}{d_{correct}}$$

$$percentage\ of\ relative\ error = \frac{d_{correct} - d}{d_{correct}} \times 100$$

What would be the reason for an error, if any?

Repeat the experiment for different masses and compare the result with $d_{correct}$ every time.

Note If there is water in the well, this method can be used to measure depth of the well till the surface of the water.

Case (ii): A body thrown vertically upwards

Consider an object of mass m thrown vertically upwards with an initial velocity u. Let us neglect the air friction. In this case we choose the vertical direction as positive y axis as shown in the Figure 2.38, then the acceleration a = –g (neglect air friction) and g points towards the negative y axis. The kinematic equations for this motion are,




Figure 2.38. An object thrown vertically

The velocity and position of the object at any time t are,

$$v = u - gt \qquad (2.20)$$

$$s = ut - \frac{1}{2} g t^2 \qquad (2.21)$$

The velocity of the object at any position y (from the point where the object is thrown) is

$$v^2 = u^2 - 2gy \qquad (2.22)$$

UNIT-2(XI-Physics_Vol-1)-1.indd 80 05-01-2022 22:15:26