For translational motion, mg sinθ is the supporting force and f is the opposing force,

$$mg\sin\theta - f = ma \qquad (5.61)$$

For rotational motion, let us take the torque with respect to the centre of the object. Then mg sinθ cannot cause torque as it passes through it but the frictional force f can set torque of Rf.

$$Rf = I\alpha$$

By using the relation, $a = r\alpha$, and moment of inertia $I = mK^2$, we get,

$$Rf = mK^2\frac{a}{R}; \quad f = ma\left(\frac{K^2}{R^2}\right)$$

Now equation (5.61) becomes,

$$mg\sin\theta - ma\left(\frac{K^2}{R^2}\right) = ma$$

$$mg\sin\theta = ma + ma\left(\frac{K^2}{R^2}\right)$$

$$a\left(1+\frac{K^2}{R^2}\right) = g\sin\theta$$

After rewriting it for acceleration, we get,

$$a = \frac{g\sin\theta}{\left(1+\frac{K^2}{R^2}\right)} \qquad (5.62)$$

We can also find the expression for final velocity of the rolling object by using third equation of motion for the inclined plane. $v^2 = u^2 + 2as$. If the body starts rolling from rest, $u = 0$. When h is the vertical height of the incline, the length of the incline s is, $s = \frac{h}{\sin\theta}$

$$v^2 = 2\frac{g\sin\theta}{\left(1+\frac{K^2}{R^2}\right)}\left(\frac{h}{\sin\theta}\right) = \frac{2gh}{\left(1+\frac{K^2}{R^2}\right)}$$

By taking square root,

$$v = \sqrt{\frac{2gh}{\left(1+\frac{K^2}{R^2}\right)}} \qquad (5.63)$$

The time taken for rolling down the incline could also be written from first equation of motion as, $v = u + at$. For the object which starts rolling from rest, $u = 0$. Then,

$$t = \frac{v}{a}$$

$$t = \left(\sqrt{\frac{2gh}{\left(1+\frac{K^2}{R^2}\right)}}\right)\left(\frac{\left(1+\frac{K^2}{R^2}\right)}{g\sin\theta}\right)$$

$$t = \sqrt{\frac{2h\left(1+\frac{K^2}{R^2}\right)}{g\sin^2\theta}} \qquad (5.64)$$

The equation suggests that for a given incline, the object with the least value of radius of gyration K will reach the bottom of the incline first.

UNIT-5(XI-Physics_Vol-1).indd 257 06-01-2022 17:48:15