Component selection	. Direct component selector -> Indirect component selector
Class member operators	:: Scope access / resolution .* Dereference ->* Dereference pointer to class member

Precedence of Operators:

Operators are executed in the order of precedence. The operands and the operators are grouped in a specific logical way for evaluation. This logical grouping is called as an Association.

The order of precedence:

( ) [ ]	Operators within parenthesis are performed first	Higher
++, --	Postfix increment / decrement	
++, --	Prefix increment / decrement	
*, /, %	Multiplication, Division, Modulus	
+, -	Addition, Subtraction	
<, <=, >, >=	Less than, Less than or equal to, Greater than, Greater than or equal to	
==, !=	Equal to, Not equal to	
&&	Logical AND	
||	Logical OR	
?:	Conditional Operator	
=	Simple Assignment	
+=, -=, *=, /=	Shorthand operators	
,	Comma operator	Lower

9.3.5 Punctuators

Punctuators are symbols, which are used as delimiters, while constructing a C++ program. They are also called as **"Separators".** The following punctuators are used in C++; most of these symbols are very similar to C and Java.

Separator	Description	Example

Curly braces { }	Opening and closing curly braces indicate the start and end of a block of code. A block of code containing more than one executable statement. These statements together are called as "compound statement"	int main ( )
		{
		int x=10, y=20, sum;
		sum = x + y;
		cout << sum;
		}

Parenthesis ( )	Opening and closing parenthesis indicate function calls and function parameters.	clrscr( ); int main ( )
Square brackets [ ]	It indicates single and multidimensional arrays.	int num[5]; char name[50];
Comma ,	It is used as a separator in an expression	int x=10, y=20, sum;

11th Std Computer Science_EM Chapter 9.indd 122 06-01-2023 15:08:45