In the above program, integer variables **num** and **avg** are declared and variable i is initialized to 1 and sum to 0. The while loop checks the condition, since i <= 5 the condition is true, a number is read from the user and this is added to sum and i is incremented by 1. Now, the condition is i <= 5 is again checked. Since 2 <=5, the second number is obtained from the user and it is added to sum. This continues, until i becomes 6, at which point the while loop terminates. After the loop termination, the avg is computed and both sum and avg are displayed.

While loop variation

A while loop may contain several variations. It can be an empty loop or an infinite loop. An empty while loop does not have any statement inside the body of the loop except null statement i.e., just a semicolon.

For example

```
int main()
{

    int i=0;
    while(++i < 10000 ):
    return 0;

}
```

This is an empty loop because the while loop does not contain any statement

In the above code, the loop is a time delay loop. A time delay loop is useful for pausing the program for some time.

A while loop may be infinite loop when no update statement is given inside the body of the loop. For example,

```
int main()
{

    int i = 0;
    while(i < =10)
      cout <<"The value of i is "<<i;
      i++;

    return 0;

}
```

This statement will be displayed infinitely because no update statement inside the body of the loop

This is not a part of the while loop statement because of missing curly braces

11th Std Computer Science_EM Chapter 10.indd 170 06-01-2023 15:09:57