Illustraion 10.16 C++ program to display numbers from 1 to 10 except 6 using continue statement

```
#include <iostream>
using namespace std;
 int main()
{
for (int i = 1; i<= 10; i++) {
if (i == 6)
continue;
else
cout<<i<< " ";
}
return 0;
}
```

Output

1 2 3 4 5 7 8 9 10

Difference between Break and Continue

Break	Continue
Break is used to **terminate** the execution of the loop.	Continue is not used to terminate the execution of loop.
It **breaks** the iteration.	It **skips** the iteration.
When this statement is executed, control will come out from the loop and executes the statement immediate after loop.	When this statement is executed, it will not come out of the loop but moves/jumps to the next iteration of loop.
Break is used with loops as well as switch case.	Continue is only used in loops, it is not used in switch case.

Hands on practice:

Write C++ program to solve the following problems :

1. Program to input a character and to print whether a given character is an alphabet, digit or any other character.
2. Program to print whether a given character is an uppercase or a lowercase character or a digit or any other character. use ASCII codes for it. The ASCII codes are as given below:

Characters	ASCII Range
0' - '9'	48 - 57
'A' - 'Z'	65 - 90
'a' - 'z'	97 - 122
other characters	0- 255 excluding the above mentioned codes.

3. Program to calculate the factorial of an integer.
4. Program to print fibonacci series i.e., 0 1 1 2 3 5 8.....

11th Std Computer Science_EM Chapter 10.indd 176 06-01-2023 15:09:58