Iteration	i <5	cout << "\n Enter value " << i+1 << "= ";	cin>>num [i];	Received value stored in memory		i++ (i=i+1)
1	5 > 0 (T)	Enter value 1 =	num[0] = 5	num[0]	5	1
2	5 > 1 (T)	Enter value 2 =	num[1] = 10	num[1]	10	2
3	5 > 2 (T)	Enter value 3 =	num[2] = 15	num[2]	15	3
4	5 > 3 (T)	Enter value 4 =	num[3] = 20	num[3]	20	4
5	5 > 4 (T)	Enter value 4 =	num[25 = [4	num[4]	25	5
6	5 > 5 (F)	Exit from Loop				

Note

In for loop, the index ***i*** is declared with an initial value 0 (zero). Since in most of the cases, the initial value of the loop index will be used as the array subscript representation.

Accessing array elements

Array elements can be used anywhere in a program as we do in case of a normal variable. The elements of an array are accessed with the array name followed by the subscript index within the square bracket.

Example:

```
cout<<num[3];
```

In the above statement, num[3] refers to the 4th element of the array and *cout* statement displays the value of num[3].

Note

The subscript in bracket can be a variable, a constant or an expression that evaluates to an integer.

// Accessing array elements

```
#include <iostream>
using namespace std;
int main()
{
        int num[5] = {10, 20, 30, 40, 50};
        int t=2;
        cout<<num[2] <<endl; // S1
        cout<<num[3+1] <<endl; // S2
        cout<<num[t=t+1]; // S3
}
```

output:

```
30
50
40
```


11th Std Computer Science_EM Chapter 12.indd 209 06-01-2023 15:10:41