Examples:

The following C++ program reads student information through keyboard and displays the same

```
#include <iostream>
using namespace std;
struct Student
{
        int  age;
        float height, weight;
} mahesh;
void main( )
{
        cout<< " Enter the age:"<<endl;
        cin>>mahesh.age;
        cout<< "Enter the height:"<<endl;
        cin>>mahesh.height;
        cout<< "Enter the weight:"<<endl;
        cin>>mahesh.weight;
        cout<< "The values entered  for Age, height and weight are"<<endl;
        cout<<mahesh.age<<     "\t"<<mahesh.height<<     "\t"<<Mahesh.
weight;
}
```

Output:

```
Enter the age:
18
Enter the height:
160.5
Enter the weight:
46.5
The values entered  for Age, height and weight are
18       160.5            46.5
```

Points to Remember:

- Structure is a user-defined which has the combination of data items with different data types
- Structure is declared using the keyword 'struct'
- Structure elements are referenced using its object name followed by dot(.) operator and then the member name
- A structure without a name/tag is called anonymous structure.
- The structure elements can be initialized either by using separate assignment statements or at the time of declaration by surrounding its values with braces.
- A structure object can also be assigned to another structure object only if both the objects are of same structure type.
- The structure declared within another structure is called a nested structure
- A structure can contain array as its member element.
- Array of structure variable can also be created.

11th Std Computer Science_EM Chapter 12.indd 222 06-01-2023 15:10:42