Note

Declaring a member function having looping construct, switch or goto statement as inline is not advisable.

14.2 Creating Objects

A class specification just defines the properties of a class. To make use of a class, the variables of that class type have to be declared. The class variables are called *object*. Objects are also called as *instance* of class.

For example

student s;

In the above statement **s** is an instance of the class **student**.

Objects can be created in two methods,

(1) Global object

(2) Local object

(1) Global Object

If an object is declared outside all the function bodies or by placing their names immediately after the closing brace of the class declaration then it is called as *Global object*. These objects can be used by any function in the program

(2) Local Object

If an object is declared with in a function then it is called *local object*. It cannot be accessed from outside the function.

Illustration 14.2 The use of local and global object

```
# include <iostream>
# include <conio.h>
using namespace std;
class add
{
  int a,b;
  public:
   int sum;
  void getdata()
  {
   a=5;
   b=10;
   sum = a+b;
  }
} a1;                    //global object
add a2;                  //global object
int main()
{
add a3;          // Local object
a1.getdata();
a2.getdata();
a3.getdata();
cout<<a1.sum;
cout<<a2.sum;
cout<<a3.sum;
return 0;
}
```

Output:

151515

ACTIVITY 2

Identify the error in the following code fragment

```
class A
{
        float x;
        void init()
        {
        A a1;
        X1.5=1;
        }};
void main()
{    A1.init(); }
```


11th Std Computer Science_EM Chapter 14.indd 237 06-01-2023 15:11:50