


Figure 3.43 Forces acting on the vehicle on a leveled circular road

Suppose the road is horizontal then the normal force and gravitational force are exactly equal and opposite. The centripetal force is provided by the force of static friction F_s between the tyre and surface of the road which acts towards the centre of the circular track,

$$\frac{mv^2}{r} = F_s$$

As we have already seen in the previous section, the static friction can increase from zero to a maximum value

$$F_s \leq \mu_s mg.$$

There are two conditions possible:

a) If $\frac{mv^2}{r} \leq \mu_s mg$, or $\mu_s \geq \frac{v^2}{rg}$ or $\sqrt{\mu_s rg} \geq v$ (Safe turn)

The static friction would be able to provide necessary centripetal force to bend the car on the road. So the coefficient of static friction between the tyre and the surface of the road determines what maximum speed the car can have for safe turn.

b) If $\frac{mv^2}{r} > \mu_s mg$, or $\mu_s < \frac{v^2}{rg}$ (skid)

If the static friction is not able to provide enough centripetal force to turn, the vehicle will start to skid.

EXAMPLE 3.24

Consider a circular leveled road of radius 10 m having coefficient of static friction 0.81. Three cars (A, B and C) are travelling with speed 7 m s^{-1}, 8 m s^{-1} and 10 ms^{-1} respectively. Which car will skid when it moves in the circular level road? (g =10 m s^{-2})

Solution

From the safe turn condition the speed of the vehicle (v) must be less than or equal to $\sqrt{\mu_s rg}$

UNIT-3(XI-Physics_Vol-1).indd 151 05-01-2022 22:18:36