www.tntextbooks.in

The tension $T = m_2 g = 5X9.8 = 49\ N$

$$T < f_s^{max}$$

The tension acting on the mass m_1 is less than the maximum static friction. So the mass m_1 will not move.

To move the mass m_1, $T > f_s^{max}$ where $T = m_2 g$

$$m_2 = \frac{\mu_s m_1 g}{g} = \mu_s m_1$$

$$m_2 = 0.9X7 = 6.3\ kg$$

If the mass m_2 is greater than 6.3 kg then the mass m_1 will begin to slide. Note that if there is no friction on the surface, the mass m_1 will move for m_2 even for just 1 kg.

The values of coefficient of static friction for pairs of materials are presented in Table 3.1. Note that the ice and ice pair have very low coefficient of static friction. This means a block of ice can move easily over another block of ice.

Table 3.1 Coefficient of Static Friction for a Pair of Materials

Material	Coefficient of Static Friction
Glass and glass	1.0
Ice and ice	0.10
Steel and steel	0.75
Wood and wood	0.35
Rubber tyre and dry concrete road	1.0
Rubber tyre and wet road	0.7

3.6.3 Kinetic Friction

If the external force acting on the object is greater than maximum static friction, the objects begin to slide. When an object slides, the surface exerts a frictional force called **kinetic friction** $\vec{f}_k$ (also called sliding friction or dynamic friction). To move an object at constant velocity we must apply a force which is equal in magnitude and opposite to the direction of kinetic friction.




Figure 3.24 Kinetic friction

Experimentally it was found that the magnitude of kinetic friction satisfies the relation

$$f_k = \mu_k N \qquad (3.28)$$

where μ_k is the coefficient of kinetic friction and N the normal force exerted by the surface on the object,

and $\mu_k < \mu_s$

This implies that starting of a motion is more difficult than maintaining it. The salient features of static and kinetic friction are given in Table 3.2.