www.tntextbooks.in

ACTIVITY

Take a glass tumbler. Fill it with water to the brim. Slide a cardboard on its rim so that no air remains in between the cardboard and the tumbler. Invert the tumbler gently. The water does not fall down.

Inference:

This is due to the fact that the weight of water in the tumbler is balanced by the upward thrust caused due to the atmospheric pressure acting on the lower surface of the cardboard that is exposed to air.

7.3.3 Pascal's law and its applications

The French scientist Blaise Pascal observed that the pressure in a fluid at rest is the same at all points if they are at the same height. Statement of Pascal's law is *If the pressure in a liquid is changed at a particular point, the change is transmitted to the entire liquid without being diminished in magnitude.*

Application of Pascal's law

Hydraulic lift




Figure 7.12 Hydraulic lift

A practical application of Pascal's law is the hydraulic lift which is used to lift a heavy load with a small force. It is a force multiplier. It consists of two cylinders A and B connected to each other by a horizontal pipe, filled with a liquid (Figure 7.12). They are fitted with frictionless pistons of cross sectional areas A_1 and A_2 ($A_2 > A_1$). Suppose a downward force F is applied on the smaller piston, the pressure of the liquid under this piston increases to $P\left(where, P = \frac{F_1}{A_1}\right)$. But according to Pascal's law, this increased pressure P is transmitted undiminished in all directions. So a pressure is exerted on piston B. Upward force on piston B is

$$F_2 = P \times A_2 = \frac{F_1}{A_1} \times A_2 \Rightarrow F_2 = \frac{A_2}{A_1} \times F_1 \quad (7.19)$$

Therefore by changing the force on the smaller piston A, the force on the piston B has been increased by the factor $\frac{A_2}{A_1}$ and this factor is called the mechanical advantage of the lift.

EXAMPLE 7.7

Two pistons of a hydraulic lift have diameters of 60 cm and 5 cm. What is the force exerted by the larger piston when 50 N is placed on the smaller piston?

Solution

Since, the diameter of the pistons are given, we can calculate the radius of the piston

$$r = \frac{D}{2}$$

Area of smaller piston, $A_1 = \pi\left(\frac{5}{2}\right)^2 = \pi(2.5)^2$

Area of larger piston, $A_2 = \pi\left(\frac{60}{2}\right)^2 = \pi(30)^2$

$$F_2 = \frac{A_2}{A_1} \times F_1 = (50N) \times \left(\frac{30}{2.5}\right)^2 = 7200\,N$$

This means, with the force of 50 N, the force of 7200 N can be lifted.