www.tntextbooks.in

Kelvin-Planck statement:

It is impossible to construct a heat engine that operates in a cycle, whose sole effect is to convert the heat completely into work. This implies that no heat engine in the universe can have 100% efficiency.

Note

According to first law of thermodynamics, in an isothermal process the given heat is completely converted into work ($Q = W$). Is it a violation of the second law of thermodynamics? No. For non-cyclic process like an isothermal expansion, the heat can be completely converted into work. But Second law of thermodynamics implies that 'In a cyclic process only a portion of the heat absorbed is converted into work'. All heat engines operate in a cyclic process.

EXAMPLE 8.24

During a cyclic process, a heat engine absorbs 500 J of heat from a hot reservoir, does work and ejects an amount of heat 300 J into the surroundings (cold reservoir). Calculate the efficiency of the heat engine?

Solution

The efficiency of heat engine is given by

$$\eta = 1 - \frac{Q_L}{Q_H}$$

$$\eta = 1 - \frac{300}{500} = 1 - \frac{3}{5}$$

$$\eta = 1 - 0.6 = 0.4$$

The heat engine has 40% efficiency, implying that this heat engine converts only 40% of the input heat into work.

8.9.1 Carnot's ideal heat engine

In the previous section we have seen that the heat engine cannot have 100% efficiency. What is the maximum possible efficiency can a heat engine have?. In the year 1824 a young French engineer Sadi Carnot proved that a certain reversible engine operated in cycle between hot and cold reservoir can have maximum efficiency. This engine is called Carnot engine.

A reversible heat engine operating in a cycle between two temperatures in a particular way is called a Carnot Engine.

The carnot engine has four parts which are given below.

i Source: It is the source of heat maintained at constant high temperature T_H. Any amount of heat can be extracted from it, without changing its temperature.

ii Sink: It is a cold body maintained at a constant low temperature T_L. It can absorb any amount of heat.

iii Insulating stand: It is made of perfectly non-conducting material. Heat is not conducted through this stand.

iv Working substance: It is an ideal gas enclosed in a cylinder with perfectly non-conducting walls and perfectly conducting bottom. A non-conducting and frictionless piston is fitted in it.

The four parts are shown in the following Figure 8.44

BPQKBR