www.tntextbooks.in

It is very important to note that after one cycle the working substance returns to the initial temperature T_H. This implies that the change in internal energy of the working substance after one cycle is zero.

8.9.2 Efficiency of a Carnot engine

Efficiency is defined as the ratio of work done by the working substance in one cycle to the amount of heat extracted from the source.

$$\eta = \frac{work\,done}{Heat\,extracted} = \frac{W}{Q_H} \qquad (8.61)$$

From the first law of thermodynamics, $W = Q_H - Q_L$

$$\therefore \eta = \frac{Q_H - Q_L}{Q_H} = 1 - \frac{Q_L}{Q_H} \qquad (8.62)$$

Applying isothermal conditions, we get,

$$Q_H = \mu R T_H \ln\left(V_2/V_1\right)$$
$$Q_L = \mu R T_L \ln\left(V_3/V_4\right) \qquad (8.63)$$

Here we omit the negative sign. Since we are interested in only the amount of heat (Q_L) ejected into the sink, we have

$$\therefore \frac{Q_L}{Q_H} = \frac{T_L \ln\left(V_3/V_4\right)}{T_H \ln\left(V_2/V_1\right)} \qquad (8.64)$$

By applying adiabatic conditions, we get,

$$T_H V_2^{\gamma-1} = T_L V_3^{\gamma-1}$$
$$T_H V_1^{\gamma-1} = T_L V_4^{\gamma-1}$$

By dividing the above two equations, we get

$$\left(\frac{V_2}{V_1}\right)^{\gamma-1} = \left(\frac{V_3}{V_4}\right)^{\gamma-1}$$

Which implies that $\frac{V_2}{V_1} = \frac{V_3}{V_4}$ (8.65)

Substituting equation (8.65) in (8.64), we get

$$\frac{Q_L}{Q_H} = \frac{T_L}{T_H} \qquad (8.66)$$

$$\therefore \text{The efficiency } \eta = 1 - \frac{T_L}{T_H} \qquad (8.67)$$

Note : T_L and T_H should be expressed in Kelvin scale.

Important results:

1. η is always less than 1 because T_L is less than T_H. This implies the efficiency cannot be 100%. It can be 1 or 100% only when T_L = *0K* (absolute zero of temperature) which is impossible to attain practically.
2. The efficiency of the Carnot's engine is independent of the working substance. It depends only on the temperatures of the source and the sink. The greater the difference between the two temperatures, higher the efficiency.
3. When $T_H = T_L$ the efficiency η =0. No engine can work having source and sink at the same temperature.
4. The entire process is reversible in the Carnot engine cycle. So Carnot engine is itself a reversible engine and has maximum efficiency. But all practical heat engines like diesel engine, petrol engine and steam engine have cycles which are not perfectly reversible. So their efficiency is always less than the Carnot efficiency. This can be stated in the form of the Carnot theorem. It is stated as follows '*Between two constant temperatures reservoirs, only Carnot engine can have maximum efficiency. All real heat engines will have efficiency less than the Carnot engine*'