www.tntextbooks.in

But $\vec{\alpha}=\frac{d^2\vec{\theta}}{dt^2}$ and therefore,

$$\frac{d^2\vec{\theta}}{dt^2}=-\frac{\kappa}{I}\vec{\theta} \qquad (10.17)$$

This differential equation resembles simple harmonic differential equation.

So, comparing equation (10.17) with simple harmonic motion given in equation (10.10), we have

$$\omega=\sqrt{\frac{\kappa}{I}}\,rad\,s^{-1} \qquad (10.18)$$

The frequency of the angular harmonic motion (from equation 10.13) is

$$f=\frac{1}{2\pi}\sqrt{\frac{\kappa}{I}}\,Hz \qquad (10.19)$$

The time period (from equation 10.12) is

$$T=2\pi\sqrt{\frac{I}{\kappa}}\ \text{second} \qquad (10.20)$$

10.3.2 Comparison of Simple Harmonic Motion and Angular Simple Harmonic Motion

In linear simple harmonic motion, the displacement of the particle is measured in terms of linear displacement $\vec{r}$ The restoring force is $\vec{F}=-k\vec{r}$, where k is a spring constant or force constant which is force per unit displacement. In this case, the inertia factor is mass of the body executing simple harmonic motion.

In angular simple harmonic motion, the displacement of the particle is measured in terms of angular displacement $\vec{\theta}$. Here, the spring factor stands for torque constant i.e., the moment of the couple to produce unit angular displacement or the restoring torque per unit angular displacement. In this case, the inertia factor stands for moment of inertia of the body executing angular simple harmonic oscillation.

Table 10.2 Comparision of simple harmonic motion and angular harmonic motion

S.No	Simple Harmonic Motion	Angular Harmonic Motion
1.	The displacement of the particle is measured in terms of linear displacement $\vec{r}$.	The displacement of the particle is measured in terms of angular displacement $\vec{\theta}$ (also known as angle of twist).
2.	Acceleration of the particle is $\vec{a}=-\omega^2\vec{r}$	Angular acceleration of the particle is $\vec{\alpha}=-\omega^2\vec{\theta}$.
3.	Force, $\vec{F}=m\vec{a}$, where m is called mass of the particle.	Torque, $\vec{\tau}=I\vec{\alpha}$, where I is called moment of inertia of a body.
4.	The restoring force $\vec{F}=-k\vec{r}$, where k is restoring force constant.	The restoring torque $\vec{\tau}=-\kappa\vec{\theta}$, where the symbol κ (Greek alphabet is pronounced as '*kappa*') is called restoring torsion constant. It depends on the property of a particular torsion fiber.
5.	Angular frequency, $\omega=\sqrt{\frac{k}{m}}$ rad s^{-1}	Angular frequency, $\omega=\sqrt{\frac{\kappa}{I}}$ rad s^{-1}