Computer memory (Main Memory and Secondary Storage)is normally represented in terms of KiloByte (KB) or MegaByte (MB). In decimal system, 1 Kilo represents 1000, that is , 10^3. In binary system, 1 KiloByte represents 1024 bytes that is 2^{10}. The following table represents the various memory sizes:

Table 2.1 Memory Size (Read 2^10 as 2 power 10)

Name	Abbr.	Size
Kilo	K	2^10 = 1,024
Mega	M	2^20 = 1,048,576
Giga	G	2^30 = 1,073,741,824
Tera	T	2^40 = 1,099,511,627,776
Peta	P	2^50 = 1,125,899,906,842,624
Exa	E	2^60 = 1,152,921,504,606,846,976
Zetta	Z	2^70 = 1,180,591,620,717,411,303,424
Yotta	Y	2^80 = 1,208,925,819,614,629,174,706,173

9GLYA

Bytes are used to represent characters in a text. Different types of coding schemes are used to represent the character set and numbers. The most commonly used coding scheme is the **American Standard Code for Information Interchange** (ASCII). Each binary value between 0 and 127 is used to represent a specific character. The ASCII value for (blank space) is 32 and the ASCII value of numeric 0 is 48. The range of ASCII values for lower case alphabets is from 97 to 122 and the range of ASCII values for the upper case alphabets is 65 to 90.

DO YOU KNOW?

The speed of a computer depends on the number of bits it can process at once. For example, a 64- bit computer can process 64-bit numbers in one operation, while a 32-bit computer break 64-bit numbers down into smaller pieces, making it slower.

2.3 Different Types of Number Systems




Figure 2.3. Number Systems

11th Std Computer Science_EM Chapter 2.indd 15 06-01-2023 15:02:38