Data type	Memory size in bytes	
	Turbo C++	Dev C++
short	2	2
unsigned short	2	2
signed short	2	2
int	2	**4**
unsigned int	2	**4**
signed int	2	**4**
long	4	4
unsigned long	4	4
signed long	4	4
char	1	1
unsigned char	1	1
signed char	1	1
float	4	4
double	8	8
long double	10	**12**

Since, Dev C++ provides 4 bytes to int and long, any one of these types can be used to handle bigger integer values while writing programs in Dev C++.

Note: sizeof( ) is an operator which gives the size of a data type.

Number Suffixes in C++

There are different suffixes for integer and floating point numbers. Suffix can be used to assign the same value as a different type. For example, if you want to store 45 in int, long, unsigned int and unsigned long int, you can use suffix letter **L** or **U** (either case) with 45 i.e. **45L** or **45U**. This type of declaration instructs the compiler to store the given values as long and unsigned. 'F' can be used for floating point values, example: 3.14F

9.13 Variables

Variables are user-defined names assigned to specific memory locations in which the values are stored. Variables are also identifiers; and hence, the rules for naming the identifiers should be followed while naming a variable. These are called as symbolic variables because these are named locations.

There are two values associated with a symbolic variable; they are **R**-value and **L**-value.

- R-value is data stored in a memory location
- L-value is the memory address in which the R-value is stored.

11th Std Computer Science_EM Chapter 9.indd 138 06-01-2023 15:08:46