If the variable value "r" is changed as **r=25;** inside the body of the function **"area"** then compiler will throw an error as **"assignment of read-only parameter 'r'"**

```
double area(const double r,const double pi=3.14)
{
        r=25;
        return(pi*r*r);
}
```

11.6 Methods of calling functions

In C++, the arguments can be passed to a function in two ways. Based on the method of passing the arguments, the function calling methods can be classified as **Call by Value method** and **Call by Reference or Address method**.

11.6.1 Call by value Method

This method copies the value of an actual parameter into the formal parameter of the function. In this case, changes made to formal parameter within the function will have no effect on the actual parameter.

Program 11.17

```
#include<iostream>
using namespace std;
void display(int x)
{
        x=x*x;
        cout<<"\n\nThe Value inside display function (x*x):"<<x;
}
int main()
{
          int a;
        cout<<"\nExample : Function call by value:";
          cout<<"\n\nEnter the Value for A :";
          cin>>a;
        display(a);
        cout<<"\n\nThe Value inside main function "<<a;
        return(0);
}
```

Output :

```
Example : Function call by value
Enter the Value for A : 5
The Value inside display function (a * a) : 25
The Value inside main function 5
```


11th Std Computer Science_EM Chapter 11.indd 194 06-01-2023 15:10:19