14.8.1 Implicit call

In this method ,the parameterized constructor is invoked automatically whenever an object is created. For example simple s1(10,20); in this for creating the object s1 parameterized constructor is automatically invoked.

14.8.2 Explicit call

In this method ,the name of the constructor is explicitly given to invoke the parameterized constructor so that the object can be created and initialized .

For example

```
simple s1=simple(10,20);        //explicit call
```

Explicit call method is the most suitable method as it creates a temporary object ,the chance of data loss will not arise.A temprory object lives in memory as long as it is being used in an expression.After this it get destroyed.

14.9 Dynamic initialization of Objects

When the initial values are provided during runtime then it is called dynamic initialization.

Illustration14.7 to illustrate dynamic initialization

```
#include<iostream>
using namespace std;
class X
{   int n;
    float avg;
    public:
    X(int p,float q)
    {  n=p;
       avg=q;  }
    void disp()
    {    cout<<"\n Roll numbe:- " <<n;
         cout<<"\nAverage :- "<<avg;          } };
int main()
{
int a ; float b;
         cout<<"\nEnter the Roll Number";
         cin>>a;
         cout<<"\nEnter the Average";
         cin>>b;
         X x(a,b);        // dynamic initialization
         x.disp();
         return 0;
}
```

Output:

```
Enter the Roll Number 1201
Enter the Average 98.6
 Roll numbe:- 1201
Average :- 98.6
```


11th Std Computer Science_EM Chapter 14.indd 243 06-01-2023 15:11:50