15.3 Constructor overloading

Function overloading can be applied for constructors, as constructors are special functions of classes. A class can have more than one constructor with different signature. Constructor overloading provides flexibility of creating multiple type of objects for a class.

Illustration 15.3 Constructor overloading

Compiler identifies overloaded constructor by its name and parameters list.

```
#include<iostream>
using namespace std;
class add
{ int num1, num2, sum;
public:
add()
{         cout<<"\n Constructor without parameters.. ";
num1= 0;  num2= 0;  sum = 0; }
add ( int s1, int s2 )
{ cout<<"\n Parameterized constructor... ";
 num1= s1;  num2=s2; sum=0; }
add (add &a)
{ cout<<"\n Copy Constructor ... ";
 num1= a.num1;
 num2=a.num2;
 sum = 0; }
void getdata()
{ cout<<"\nEnter data ... "; cin>>num1>>num2; }
void addition()
{ sum=num1+num2; }
void putdata() {
cout<<"\n The numbers are..";
cout<<num1<<'\t'<<num2;
cout<<"\n The sum of the numbers are.. "<< sum; } };
int main() {
add a, b (10, 20) , c(b);
a.getdata();
a.addition();
b.addition();
c.addition();
cout<<"\n Object a : ";
a.putdata();
cout<<"\n Object b : ";
b.putdata();
cout<<"\n Object c.. ";
c.putdata();
return 0; }
```


11th Std Computer Science_EM Chapter 15.indd 252 06-01-2023 15:12:06