எடுத்துக்காட்டு 9.5: C++ தரவினத்தின் அளவை கண்டறிவதற்கான நிரல்

```
#include <iostream>
using namespace std;
int main()
{
        short a;
        unsigned short b;
        signed short c;
        int d;
        unsigned int e;
        signed int f;
        long g;
        unsigned long h;
        signed long i;
        char j;
        unsigned char k;
        signed char l;
        float m;
        double n;
        long double p;
        cout << "\n Size of short = " << sizeof(a);
        cout << "\n Size of unsigned short = " << sizeof(b);
        cout << "\n Size of signed short = " << sizeof (c);
        cout << "\n Size of int = " << sizeof(d);
        cout << "\n Size of unsigned int = " << sizeof(e);
        cout << "\n Size of signed int = " << sizeof(f);
        cout << "\n Size of long = " << sizeof(g);
        cout << "\n Size of unsigned long = " << sizeof(h);
        cout << "\n Size of signed long = " << sizeof(i);
        cout << "\n Size of char = " << sizeof(j);
        cout << "\n Size of unsigned char = " << sizeof(k);
        cout << "\n Size of signed char = " << sizeof(l);
        cout << "\n Size of float = " << sizeof(m);
        cout << "\n Size of double = " << sizeof(n);
        cout << "\n Size of long double = " << sizeof(p);
}
```

வெளியீடு: (Dev C++ ல் தொகுத்து இயக்கப்படுகிறது)

```
Size of short = 2
Size of unsigned short = 2
Size of signed short = 2
Size of int = 4
Size of unsigned int = 4
Size of signed int = 4
Size of unsigned int = 4
Size of signed int = 4
Size of long = 4
Size of unsigned long = 4
Size of signed long = 4
Size of char = 1
Size of unsigned char = 1
Size of signed char = 1
Size of float = 4
Size of double = 8
Size of long double = 12
```

குறிப்பு:

sizeof( ) எனும் செயற்குறி தரவினத்தின் அளவை வெளியீடாக காட்டும்.

C++ - ல் எண்களின் பின்னொட்டு

முழு எண் மற்றும் மிதப்புப்புள்ளி எண்களுக்கு வேறுபட்ட பின்னொட்டுகள் பயன்படுகின்றன. ஒரே மதிப்பை, பல்வேறு தரவினமாக எடுத்துக்காட்டாக, 45 என்ற மதிப்பை long, unsigned int மற்றும் unsigned long int (ஆங்கில சிறிய அல்லது பெரிய எழுத்து) பின்னொட்டாக சேர்க்க வேண்டும். அதாவது, 45L அல்லது 45U என இவ்வாறு குறிப்பிடுவது, கொடுக்கப்பட்ட மதிப்புகளை long மற்றும் unsigned என எடுத்துக்கொள்ள வேண்டும் என்று நிரல் பெயர்ப்பிக்கு கட்டளையிடுவதாகும். அதேப் போன்று, மிதப்புப் புள்ளி எண்களைக் குறிப்பிட F என்ற எழுத்தை பயனபடுத்த வேண்டும்.

Chapter 9.indd 143 20-12-2022 15:36:50