எடுத்துக்காட்டு: Caret(^) செயற்குறியைப் பயன்படுத்தி சமச்சீரான வேறுபாட்டை கண்டறியும் நிரல்.

```
set_A={'A', 2, 4, 'D'}
set_B={'A', 'B', 'C', 'D'}
print(set_A ^ set_B)
```

வெளியீடு

```
{2, 4, 'B', 'C'}
```

எடுத்துக்காட்டு: Symmetric difference செயற்கூறைப் பயன்படுத்தி சமச்சீரான வேறுபாட்டை கண்டறியும் நிரல்

```
set_A={'A', 2, 4, 'D'}
set_B={'A', 'B', 'C', 'D'}
print(set_A.symmetric_difference(set_B))
```

வெளியீடு

```
{2, 4, 'B', 'C'}
```

9.3.4 set பயன்படுத்தப்பட்ட நிரல்

நிரல் 1: பகா எண்களைக் கொண்ட ஒரு Set, இரட்டைப்படை எண்களை கொண்ட மற்றொரு Set உருவாக்குவதற்கான நிரல் (ஒட்டு, வெட்டு, வேறுபாடு, சமச்சீரான வேறுபாடு போன்ற செயற்பாடுகளுக்கான விடையை நிரூபிக்கவும்).

எடுத்துக்காட்டு

```
even=set([x*2 for x in range(1,11)])
primes=set()
for i in range(2,20):
        j=2
        f=0
        while j<=i/2:
                if i%j==0:
                        f=1
                j+=1
        if f==0:
                primes.add(i)
print("Even Numbers: ", even)
print("Prime Numbers: ", primes)
print("Union: ", even.union(primes))
print("Intersection: ", even.intersection(primes))
print("Difference: ", even.difference(primes))
print("Symmetric Difference: ", even.symmetric_difference(primes))
```


12th Computer Science_TM Chapter 9.indd 165 11-01-2023 12:39:02