Step 3 – Compare with all elements in the sorted sub-list

Step 4 – Shift all the elements in the sorted sub-list that is greater than the value to be sorted

Step 5 – Insert the value

Step 6 – Repeat until list is sorted

44	16	83	07	67	21	34	45	10	Assume 44 is a sorted list of 1 item
16	44	83	07	67	21	34	45	10	inserted 16
16	44	83	07	67	21	34	45	10	inserted 83
07	16	44	83	67	21	34	45	10	inserted 07
07	16	44	67	83	21	34	45	10	inserted 67
07	16	21	44	67	83	34	45	10	inserted 21
07	16	21	34	44	67	83	45	10	inserted 34
07	16	21	34	44	45	67	83	10	inserted 45
07	10	16	21	34	44	45	67	83	inserted 10

At the end of the pass the insertion sort algorithm gives the sorted output in ascending order as shown below:

07	10	16	21	34	44	45	67	83

4.6. Dynamic programming

Dynamic programming is an algorithmic design method that can be used when the solution to a problem can be viewed as the result of a sequence of decisions. Dynamic programming approach is similar to divide and conquer. The given problem is divided into smaller and yet smaller possible sub-problems.

Dynamic programming is used whenever problems can be divided into similar sub-problems. so that their results can be re-used to complete the process. Dynamic programming approaches are used to find the solution in optimized way. For every inner sub problem, dynamic algorithm will try to check the results of the previously solved sub-problems. The solutions of overlapped sub-problems are combined in order to get the better solution.

Steps to do Dynamic programming

- The given problem will be divided into smaller overlapping sub-problems.
- An optimum solution for the given problem can be achieved by using result of smaller sub-problem.
- Dynamic algorithms uses Memoization.

Note

Memoization or memoisation is an optimization technique used primarily to speed up computer programs by storing the results of previous function calls and returning the cached result when the same inputs occur again.

12th Computer Science_EM Chapter 4.indd 41 21-12-2022 15:55:01