The Syntax conditional operator is,

Variable Name = [on_true] if [Test expression] else [on_false]

Example :

```
min= 49 if 49<50 else 50 # min = 49
min= 50 if 49>50 else 49 # min = 49
```

Program 5.5 To test Conditional (Ternary) Operator:

```
# Program to demonstrate conditional operator
        a, b = 30, 20
# Copy value of a in min if a < b else copy b
        min = a if a < b else b
        print ("The Minimum of A and B is ",min)
# End of the Program
```

Output:

```
        The Minimum of A and B is  20
```

5.7.4 Delimiters

Delimiters are sequence of one or more characters used to specify the boundary between seperate, independent regions in plain text or other data streams. Python uses the symbols and symbol combinations as delimiters in expressions, lists, dictionaries and strings. Following are the delimiters.

(	)	[	]	{	}
,	:	.	‘	=	;

5.7.5 Literals

Literal is a raw data given to a variable or constant. In Python, there are various types of literals.

1) Numeric
2) String
3) Boolean

(i) Numeric Literals

Numeric Literals consists of digits and are immutable (unchangeable). Numeric literals can belong to 3 different numerical types Integer, Float and Complex.

12th Computer Science_EM Chapter 5.indd 61 26-12-2022 17:27:29