| Syntax | Description | Example |
|---|---|---|
| count(str, beg, end) | Returns the number of substrings occurs within the given range. Remember that substring may be a single character. Range (beg and end) arguments are optional. If it is not given, python searched in whole string. Search is case sensitive. | >>> str1="Raja Raja Chozhan"<br>>>> print(str1.count('Raja'))<br>***2***<br>>>> print(str1.count('r'))<br>***0***<br>>>> prin***t(str1.count('R'))***<br>2<br>>>> print(str1.count('a'))<br>***5***<br>>>> print(str1.count('a',0,5))<br>***2***<br>>>> print(str1.count('a',11))<br>***1*** |
| ord(char ) | Returns the ASCII code of the character. | >>> ch = 'A'<br>>>> print(ord(ch))<br>65<br>>>> print(***ord('B'))***<br>66 |
| chr(ASII) | Returns the character represented by a ASCII. | >>> ch=97<br>>>> print(chr(ch))<br>***a***<br>>>> print(chr(87))<br>***W*** |

## 8.10 Membership Operators

The '**in**' and '**not in**' operators can be used with strings to determine whether a string is present in another string. Therefore, these operators are called as Membership Operators.

### Example

```
str1=input ("Enter a string: ")
str2="chennai"
if str2 in str1:
        print ("Found")
else:
        print ("Not Found")
```

**Output : 1**

```
Enter a string: Chennai G HSS, Saidapet
Found
```

**Output : 2**

```
Enter a string: Govt G HSS, Ashok Nagar
Not Found
```



12th Computer Science_EM Chapter 8.indd 125 21-12-2022 15:28:39