Application Programmers or Software Developers

This user group is involved in developing and designing the parts of DBMS.

End User

All modern applications, web or mobile, store user data. Applications are programmed in such a way that they collect user data and store the data on DBMS systems running on their server. End users are the one who store, retrieve, update and delete data.

Database designers: are responsible for identifying the data to be stored in the database for choosing appropriate structures to represent and store the data.

11.7 Difference between DBMS and RDBMS

Basis of Comparison	DBMS	RDBMS
Expansion	Database Management System	Relational DataBase Management System
Data storage	Navigational model ie data by linked records	Relational model (in tables). ie data in tables as row and column
Data redundancy	Present	Not Present
Normalization	Not performed	RDBMS uses normalization to reduce redundancy
Data access	Consumes more time	Faster, compared to DBMS.
Keys and indexes	Does not use.	used to establish relationship. Keys are used in RDBMS.
Transaction management	Inefficient, Error prone and insecure.	Efficient and secure.
Distributed Databases	Not supported	Supported by RDBMS.
Example	Dbase, FoxPro.	SQL server, Oracle, mysql, MariaDB, SQLite, MS Access.

Database normalization was first proposed by ***Dr. Edgar F Codd*** as an integral part of RDBMS in order to reduce data redundancy and improve data integrity. These rules are known as E F Codd Rules.