INSERT INTO Student(Admno, Name, Place) VALUES (103, 'Ayush', 'Delhi');

103	Ayush	M	18	Delhi

The above command adds the following record with default values of 'M' for Gender and Age as 18.

INSERT INTO Student (Admno, Name, Place) VALUES (104, 'Abinandh', 'Chennai');

104	Abinandh	M	18	Chennai

The student table will have the following data:

Admno	Name	Gender	Age	Place
100	Ashish	M	17	Chennai
101	Adarsh	M	18	Delhi
102	Akshith	M	17	Bangalore
103	Ayush	M	18	Delhi
104	Abinandh	M	18	Chennai

The fields that are not given in the INSERT command will take default values, if it is defined for them, otherwise NULL value will be stored.



In the INSERT command the fields that are omitted will have either default value defined or NULL value.

12.7.3.2 DELETE COMMAND

The **DELETE** command permanently removes one or more records from the table. It removes the entire row, not individual fields of the row, so no field argument is needed. The **DELETE** command is used as follows :

DELETE FROM table-name WHERE condition;

For example to delete the record whose admission number is 104 the command is given as follows:

DELETE FROM Student WHERE Admno=104;

104	Abinandh	M	18	Chennai

The following record is deleted from the Student table.

To delete all the rows of the table, the command is used as :

DELETE FROM Student;

The table will be empty now and could be destroyed using the DROP command (Discussed in section 12.7.4.3).

12th Computer Science_EM Chapter 12.indd 209 22-12-2022 11:54:47